

**WK S 0,8x4,0**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Interchangeable bits for torque screwdriver**

Drive output acc. to DIN 5264, ISO 2380/1

**General ordering data**

Type	WK S 0,8x4,0
Order No.	<a href="#">9918550000</a>
Version	Screwdriver insert, Blade width (B): 4 mm, 175 mm, Blade thickness (A): 0.8 mm
GTIN (EAN)	4032248388912
Qty.	1 pc(s).

**WK S 0,8x4,0****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****Dimensions and weights**

Width	175 mm	Width (inches)	6.89 inch
Height	4 mm	Height (inches)	0.157 inch
Depth	4 mm	Depth (inches)	0.157 inch
Weight	22 g	Net weight	25 g

**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

**Screwing tools**

Blade length	175 mm	Blade thickness (A)	0.8 mm
Blade width (B)	4 mm	Form	Slotted

**Classifications**

ETIM 3.0	EC001395	ETIM 4.0	EC001395
ETIM 5.0	EC001395	ETIM 6.0	EC002116
UNSPSC	27-11-28-14	eClass 5.1	21-04-04-02
eClass 6.2	21-04-92-21	eClass 7.1	21-04-04-90
eClass 8.1	21-04-04-90	eClass 9.0	21-04-04-00
eClass 9.1	21-04-04-90		

**Approvals**

Approvals

**Downloads**

Brochure/Catalogue [CAT 3 HDC 17/18 EN](#)  
[CAT 6 TOOLS 15/16 EN](#)  
[CAT 5 ENCL 17/18 EN](#)