



3P -20P

45	47.2			19A	19
42.5	44.7			18A	18
40	42.2			17A	17
15	17.2			07A	7
10	12.2	22 03 1051		3022 05A	5
A	(B)	POLYBAG PACKAGE オーダー番号 ORDER NO.		MODEL NO.	極数 CKT.

NOTES:

1. 材料 MATERIAL
 ウェハ: ポリアミド、UL94V-0 色: ナチュラル(白)
 WAFER: POLYAMIDE, UL94V-0 COLOR: NATURAL(WHITE)
 ピン: 黄銅、銅下地銅メッキ
 PIN: BRASS, TIN OVER COPPER PLATING
2. ウェハのソリは、長さ 25.4mm に対して 0.2mm MAX.
 CAMBER MUST BE WITHIN 0.2mm MAX. PER 25.4mm
3. () 内寸法は参考値
 () REFERENCE DIMENSIONS
4. ELV 及び RoHS 適合品
 ELV AND RoHS COMPLIANT

REVISED IEC NO: J2016-1312 DRWN:MI SOGAYA 2016/06/28 CHKD:Y01TO 2016/06/28 APPR:Y01TO 2016/06/30	QUALITY SYMBOLS □ = 0 CRITICAL ⊠ = 0 MAJOR ▽ = 0 ZERO DEFECT ▽ = 0 S.P.C.	GENERAL TOLERANCES (UNLESS SPECIFIED) DIMENSIONS ± 0.1 ANGULAR ± 3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION STYLE MM ONLY	SCALE 4:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	DRAWN BY: KWASHIO DATE: 2012/01/21 CHECKED BY: KASAKAWA DATE: 2013/08/13 APPROVED BY: NUKITA DATE: 2015/03/20		TITLE WAFER ASSY KK 2.5MM			
	MATERIAL NO. SEE CHART		DOCUMENT NO. SD-3022-001		SHEET NO. 1 OF 1	
	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					