ſ	D I	г	m	I	D	0		σ	A		_
4		S					YOUT SHOWN AS EXAM	PLE			4
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown as e	Connector dimension Dim Nominal								
2	-Shell Material: Aluminium-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimu		A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g			due to a use the Specifications	not be liable for any nor of the Products which o s issued by either of the ional recommendation, Country FR	does not comply w Parties or by a thi technical notice.) Jurisdiction a	vith ird party		2
	-Durability : 500 Mating cycles -Delivered without Souriau contacts -Temperature Range : -65°C to +175°C Salt Spray				A 01-10-20	P 016 First Release	PN: 8D711Z02	PAL			
_	-Salt Spray : 500 hours -Mass : 17.18 g ± 10%				ISS DATE Designed By:	Latest modification Date:			TOMER DRAWING	MOD N°	
_ -	BASIC SERIES: 8D 7 - 11 SHELL TYPE : Jam nut Receptacle - - - -	Z 02 P A L	Delivered W/		SCALE NA		General linear Tolerances: ±	NI	PRDS / PROJECT 859 This document is the pro	perty of	1
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : Z = Black Zinc Nickel		ORIEN CONTACT TYPE : PIN(50 CONTACT LAYC		SOURIA FORMAT A3		SOURIAU.CON SOURIAU DI 8D711Z02P	RG N°	SOURIAU it must not be reproduc ommunicated without pe		-
	H G	F	E	/	D	C		В	A		

Г	I D	т			
4	Contact Layout		Panel cutout JAM NUT RECEPTACLE (TYPE		4
	Contacts (Insert arrangement 11-2) Contact position ID Contact location (mm) A +.095 (2.41) +.000 (.00) B 095 (2.41) +.000 (.00) Shell Arrangement no. Number of contacts Size Service rating Contact location 11 -2 2 16 I All			<u>minal</u> +0/-0.25	
2				+0.25/-0	3
			due to a use of the Specifications issu	be liable for any non-conformity or damage the Products which does not comply with ued by either of the Parties or by a third party recommendation, technical notice.)	
N			A 01-10-2016 First Release		2
			ISS DATE Latest modification -	by MOD N°	
			Designed By: Date:	CUSTOMER DRAWING	
			TITLE	Aluminium Receptacle 8D series	
				General linear NPRDS / PROJECT Tolerances: 859 ± This document is the property of	1
			SOURIAU WWW.SC	SOURIAU it must not be reproduced or communicated without permission	
				OURIAU DRG N° SHEET	
		E E		BD711Z02PAL-C 2/2	
	H I G I	F I E	D C	B A	