





LDD Comm COG, Ceramic, 0.022 uF, 5%, 200 VDC, COG





Click here for the 3D model.

Dimensions	
D	6.35mm +/-0.381mm
L	12.7mm +/-0.508mm
LL	38.1mm MIN
F	0.64mm +0.1/-0.025mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	25

	General Information		
	Series	LDD Comm COG	
	RoHS	No	
	Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
	SCIP Number	132e61c0-5a2b-4355-a818-8e6ea80949b5	
	Termination	Lead (SnPb)	
	AEC-Q200	No	
	Notes	Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.	

Specifications				
Capacitance	0.022 uF			
Capacitance Tolerance	5%			
Voltage DC	200 VDC			
Dielectric Withstanding Voltage	500 VDC			
Temperature Range	-55/+125°C			
Temperature Coefficient	COG			
Dissipation Factor	0.1% 1 kHz 25C			
Insulation Resistance	45 MOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.