


HT06CW224KN

Obsolete

HP LDD Indust X7R HT200C, Ceramic, 0.22 uF, 10%, 100 VDC, X7R, Commercial, High Temperature, Lead Spacing = 5.08mm



Click here for the 3D model.

Dimensions	
L	7.62mm MAX
Н	7.62mm MAX
Т	3.81mm MAX
S	5.08mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Pacl	kad	ina	Sn	ecif	icat	tions

Packaging Waffle, Tray

General Information				
HP LDD Indust X7R HT200C				
Radial				
Commercial, High Temperature				
LDD High Temperature 200C				
No				
▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.				
Nickel				
No				

Specifications				
Capacitance	0.22 uF			
Capacitance Tolerance	10%			
Voltage DC	100 VDC			
Temperature Range	-55/+200°C			
Temperature Coefficient	X7R			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.