


MPX1D2213L150

Aliases (UPI2X12213L150)

KEMET, MPX, Power, 15 uH, 20%, 2213(9088)



General Information		
Series	MPX	
Style	SMD	
Chip Size	2213(9088)	
Description	Surface Mount Inductor	
Features	Power Inductors	
RoHS	Yes	
Core	Composite	
Miscellaneous	40 (K) Temperature Rise Max.	

Click here for the 3D model.

Dimensions	
L	22mm +/-0.5mm
W	22mm +/-0.5mm
Т	13mm MAX
LL	5mm NOM
G	18.5mm NOM

Specifications	
Inductance	15 uH
Inductance Tolerance	20%
Temperature Range	-55/+155°C
Shielded	Yes
Current	27.5 A (Irms, 40C Rise By Self Heating), 22 A (Isat, 20% Drop In Inductance), 30 A (Isat, 30% Drop In Inductance)
DC Resistance	6.8 mOhms
Self-Resonant Frequency	4 MHz

Packaging Specifications		
Packaging	T&R, 330mm	
Packaging Quantity	50	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.