



Main

Anwendung	Multi-purpose
Range	Spacial
Product or Component Type	Rail
Accessory / separate part category	Mounting accessory
Type of rail	Asymmetrical DIN rail
Enclosure nominal dimensions	-
Range compatibility	Spacial Thalassa
Device composition	1 rail
Quantity per Set	Set of 10

Complementary

Material	Galvanised steel
Surface Finish	Perforated
Fixing mode	By fixing element - structure of enclosure
Adjustment	Continuous adjustment Pitch 25 mm
Length	78.74 in (2000 mm)
Height	Nominal 0.59 in (15 mm)
Width	Nominal 1.26 in (32 mm)
Thickness	0.06 in (1.5 mm)

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480180200
Nbr. of units in pkg.	1
Package weight(Lbs)	2.87 lb(US) (1.3 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.59 in (1.5 cm)
Package 1 width	1.26 in (3.2 cm)
Package 1 Length	78.74 in (200 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------