

## Specification Sheet

Part Number: 558-00502



Adhesive Labels, Solid Color Continuous Roll, Reflective, 2.0" x 250', UVStable PET, Red, 250ft/roll

**Article Number**

558-00502

**Type**

HT2RDHB250

**Color**

Red (RD)

**Features & Benefits**

- Continuous Polyester Labels are made with UV stable materials for long outdoor life.
- Labels use UV stable permanent ink.
- Continuous polyester is provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems.

**Quantity Per**

roll

**Product Description**

Continuous Polyester Labels are made with UV stable materials for long outdoor life. The labels are made with UV stable permanent inks for long term fade resistance. The Continuous Polyester is provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems.

<b>Short Description</b>	Adhesive Labels, Solid Color Continuous Roll, Reflective, 2.0" x 250', UVStable PET, Red, 250ft/roll
<b>Global Part Name</b>	HT2RDHB250-840/281-RD
<b>Technical Description</b>	Solid Colored Continuous Roll, Reflective, 2.0" X 250', Red
<b>Length L (Imperial)</b>	250.0
<b>Length L (Metric)</b>	76.2
<b>Variant</b>	3.2mil, 50lb bleached kraft paper
<b>Width W (Imperial)</b>	2.0
<b>Width W (Metric)</b>	50.8
<b>Thickness T (Metric)</b>	64.0
<b>Width of Liner (Metric)</b>	50.8
<b>Width of Liner (imperial)</b>	2.0
<b>Material</b>	Type 840/281, Polyester (PET), UV Stable, Clear Polyester Laminate
<b>Material Shortcut</b>	840/281
<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	No

<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature (Metric)</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	CSA 66956 NEC2014 IFC 2012 ANSI Standard Z535.4 UL 969 NEC2011
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	250
<b>Package Quantity (Metric)</b>	76.20
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	0.68
<b>Weight (Imperial)</b>	1.48