	т п		0	8 }	
Z Z M Z M Z M Z M Z M Z M Z M Z M Z M Z				In the	
	Keying Shown as example		LAYOUT SHOWN AS EXAMP	LE	
CHARACTERISTICS					
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal				
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	ØS35.7 MaxZ31 MaxVV THREADM25x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Contact Plating : Gold over copper Alloy 0.8μm minimum		<u> </u>	Country FR	Jurisdiction & Control List Not Listed	
-Durability : 500 Mating cycles -Delivered without Souriau contacts			PN: 8D517W06	SBL	
-Temperature Range : -65°C to +175°C		A 17-10-2016	First Release		
-Salt Spray : 500 hours		ISS DATE	Latest modification - by	MOD	
Mass : 29.9 g ± 10%		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	TLE Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 17 W SHELL TYPE : Plug with RFI Shielding	06 S B L Delivered W/O	SCALE .	General linear Tolerances:	NPRDS / PROJECT <b>859</b>	
CONTACT TYPE : Standard Crimp Contact	ORIENT	ATION : B SOURIAU		This document is the property of SOURIAU it must not be reproduced or	
SHELL SIZE : 17	CONTACT TYPE : SOCKET(500			communicated without permission	
		IT · 17-06 FORMAT		G N° SHEE	ET .
PLATING : W = Olive drab Cadmium	CONTACT LAYOU	A3	SOURIAU DR 8D517W06S		

r	Ŧ	G	г	m		0
		Contact Layout				
4		+Y				
	-x -	$ \stackrel{\mathbb{E}}{\longrightarrow} \stackrel{\mathbb{A}}{\oplus} $ $ \stackrel{\mathbb{P}}{\oplus} \stackrel{\mathbb{E}}{\oplus} \stackrel{\mathbb{B}}{\oplus} $				
		C⊕ €Y				
	Conta	Contacts           (Insert arrangement 17-6)           act         Location           X-axis         Y-axis           (mm)         (mm)				
	A B C D E	+.121 (3.07) +.209 (5.31) +.241 (6.12) +.000 (0.00) +.000 (0.00)241 (6.12) 241 (6.12) +.000 (0.00)				
ယ	Shell Arrangement Nur size no. co					
	-					SOURIAU shall not be liable for ar
						due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D517V
					A 17-10-20	016 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
<b>_</b>					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIAL 8D517W
L	Н	G	F	E	D	C

				4		
				<u> </u>		
				3		
	non-conformit h does not co					
s which does not comply with er of the Parties or by a third party indation, technical notice.)						
	, teenneur m					
untry FR	Jurisd	liction & Control List Not Listed		2		
7W(	06SBL					
		CUSTOMER DRAWING	MOD N°			
niniu	um Plug 8					
ar		NPRDS / PROJECT		-		
:	859					
J.COM This document is the property of SOURIAU it must not be reproduced or						
it must not be reproduced or communicated without permission						
	DRG N°		SHEET			
N0	6SBL-C	-	2/2	J		
	В	I A				

A

ω