	т <u>О</u> т	m I	C)	0	B	A		
4	R 22.6 Max () () () () () () () () () () () () () (<image/>	OUT SHOWN AS EXAMPLE			4
	Ke CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	eying Shown as example Connector dimension Dim Nominal							
N	-Shell Material: Aluminium-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles	A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g			due to a use the Specifications (professio	not be liable for any non-confo of the Products which does no issued by either of the Parties onal recommendation, technic Country Ju FR PN: 8D711Z01BD	t comply with or by a third party		2
_	-Delivered with Souriau contacts and Accessories-Temperature Range: -65°C to +175°C-Salt Spray: 500 hours-Mass: 21.11 g ± 10%			A 01-10-20 ISS DATE Designed By:	16 First Release		CUSTOMER DRAWING	MOD N°	
	BASIC SERIES: 8D 7 - 11 Z 01 SHELL TYPE : Jam nut Receptacle	B D ORIENT	0 Matings)	TITLE SCALE NA SOURIA	U www.	Aluminium Recept	NPRDS / PROJECT 859 This document is the pro SOURIAU it must not be reprodu communicated without p	iced or	1
	H G F		D	A3	С	SOURIAU DRG N 8D711Z01BD-0 B		1/2	

O1 Image: Construction of the constructi	4
$ \begin{array}{c} $	4
11-01 Image: Constraint of the second se	3
SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)	
Country Jurisdiction & Control List FR Not Listed	2
PN: 8D711Z01BD	
A 01-10-2016 First Release	
ISS DATE Latest modification - by Designed By: Date: CUSTOMER DRAWING	MOD N°
TITLE Aluminium Receptacle 8D series	
SCALE General linear NPRDS / PROJECT NA Tolerances: 859	
SOURIAU WWW.SOURIAU.COM it must not be reproducted without p	iced or
FORMAT SOURIAU DRG N°	SHEET
H G F E D C B A	2/2