


PCB-2011



13 PC-Kontaktbohrungen Ø1+0,1

Ansicht ist auf der Steckseite Stift-Stecker gezeichnet.

Fuer Steckseite Buchen-Stecker ist das Bohrild spiegelbildlich zur Hauptachse (▼)

13 PC-contact holes Ø1+0,1

View on mating face of pin-connector

For mating face of socket-connector the hole pattern is symmetrically to the main axis (▼)

Winkelverdrehung: keine
angular rotations: none

Bohrung / hole	Lage / position		Bohrung / hole	Lage / position	
	X-Achse / X-axis ±0,05	Y-Achse / Y-axis ±0,05		X-Achse / X-axis ±0,05	Y-Achse / Y-axis ±0,05
A	0,00	-2,60	H	3,50	0,00
B	-3,50	4,05	J	3,95	-5,20
C	3,50	4,05	K	7,00	-2,05
D	-3,95	-5,20	L	0,00	6,05
E	0,00	2,05	M	-7,00	2,05
F	7,00	2,05	N	-7,00	-2,05
G	-3,50	0,00			

Ø1 H15	
Gehäuseform / CA 02L	shell type / CA 20L
34	45

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
Specification and Dimensions subject to change
Drawings illustrate normal insulator positioning

Material Specification:
Shell Material: Aluminium alloy
Shell Plating: Olive drab chromate over cadmium (conductive)
Insulator Material: CR-Elastomere
Contact Material: Copper alloy
Contact Plating: Hard silver

all dimensions are in mm
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
CUSTOMER



description CA20L20-11S-B
Box mounting receptacle

Engineered for life
ITT CANNON GmbH
D - 71384 Weinstadt/Germany

PCB Ø 0,76 / Socket / Layout: 20-11

© All rights reserved. Reproduction or issue to third in any form
whenever is only permitted with written authorization of ITT Cannon



page
2/2

revision
1730 14. May 19