

# ATGBICS JL275A-C network transceiver module Fiber optic 100000 Mbit/s QSFP 1310 nm

**Brand :** ATGBICS

**Product code:** JL275A-C

**Product name :** JL275A-C



HPE Compatible Transceiver QSFP28 100GBase-LR4 1310nm SMF 10km LC DOM

ATGBICS JL275A-C network transceiver module Fiber optic 100000 Mbit/s QSFP 1310 nm:

ATGBICSJL275A 100GBase-LR4 QSFP28 supports a distance of up to 10km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of HPE JL275A= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



ATGBICS JL275A-C. SFP transceiver type: Fiber optic, Maximum data transfer rate: 100000 Mbit/s, Interface type: QSFP. Product colour: Silver, Housing material: Metal, Country of origin: China. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 4 W. Width: 13.5 mm, Depth: 72.4 mm, Height: 18.4 mm. Number of products included: 1 pc(s), Package type: Box

| Performance                          |                      | Features                          |             |
|--------------------------------------|----------------------|-----------------------------------|-------------|
| SFP transceiver type *               | Fiber optic          | Brand compatibility               | HP          |
| Maximum data transfer rate *         | 100000 Mbit/s        | <b>Power</b>                      |             |
| Interface type *                     | QSFP                 | Input voltage                     | 3.3 V       |
| Single-mode fiber (SMF) supported    | ✓                    | Maximum voltage                   | 3.5 V       |
| Multi-mode fiber (MMF) supported     | ✗                    | Power consumption (typical)       | 4 W         |
| Fiber optic connector                | LC                   | <b>Operational conditions</b>     |             |
| SFP transceiver standard             | LR4                  | Maximum operating temperature     | 70 °C       |
| Maximum transfer distance            | 10000 m              | Operating temperature (T-T)       | 0 - 70 °C   |
| Wavelength                           | 1310 nm              | Storage temperature (T-T)         | -40 - 85 °C |
| Ethernet LAN                         | ✓                    | Operating relative humidity (H-H) | 0 - 95%     |
| Ethernet interface type              | 100 Gigabit Ethernet | Storage relative humidity (H-H)   | 0 - 95%     |
| Digital Diagnostics Monitoring (DDM) | ✓                    | <b>Weight &amp; dimensions</b>    |             |
| <b>Features</b>                      |                      | Width                             | 13.5 mm     |
| Product colour                       | Silver               | Depth                             | 72.4 mm     |
| Housing material                     | Metal                | Height                            | 18.4 mm     |
| Plug and Play                        | ✓                    | Weight                            | 42 g        |
| Hot-Plug support                     | ✓                    | <b>Packaging data</b>             |             |
| Hot-swap                             | ✓                    | Number of products included       | 1 pc(s)     |
| Easy to install                      | ✓                    | Package type                      | Box         |
| Country of origin                    | China                | <b>Technical details</b>          |             |
|                                      |                      | Sustainability certificates       | RoHS        |



5056468759719

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.