



- NOTES: VALID UNLESS OTHERWISE SPECIFIED
1. GENERAL:
    - a. MATERIAL: PBT 30% GLASS FILLED, NO REGRIND ALLOWED, GM MATERIAL SPECIFICATION: GMP.PBT.010 - FLAMMABILITY PER GMW3232.
    - b. PACKAGING SPECIFICATION PER MOLEX DRAWING, PLEASE REFER TO THE TABLE
    - 12 c. LETTERING SHALL BE 0.20 MAX RAISED. THIS INCLUDES RECYCLING CODE, CAVITY ID, & VENDOR IDENTIFICATION.
    - d. LASER WELD SURFACE ALL AROUND ON BOTH TOP AND BOTTOM SURFACES NO PART LINES, SURFACE DEFECTS, CONTAMINATION, EJECTOR MARKS, COLD SLUGS OR KNIT LINES ALLOWED.
    - e. FOR MATING MODULE SEE DRAWING NUMBER SD-34843-001
    - f. INDICATED DIMENSIONS CAN BE MEASURED WITH [A] FIXTURED FLAT.
    - g. NO EXTERNAL MOLD RELEASE AGENTS ALLOWED
    - h. AVERAGE L.E.T. VALUE TO BE BETWEEN 13-25% WHEN MEASURED AT THE FOUR LOCATIONS DEFINED BY THE AGREED UPON TEST FIXTURE.
    - i. PART WEIGHT IS 24.5g.

AUTOLV P/N	MOLEX P/N BEFORE PACKAGING	MOLEX P/N AFTER PACKAGING	MOLEX PACKAGING SPECIFICATION
622657300A	348430400	348430401 348430402	PK-34843-002 PK-34843-003

INSPECTION BALLOON NUMBER LOG			
PER DRAWING REVISION: A8			
LAST BALLOON NUMBER USED: 11			
ADDED BALLOON NUMBERS:			
REMOVED BALLOON NUMBERS:			

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
	mm	INCH	MM ONLY	DATE			
▽=0	4 PLACES ± ---	± ---	DRAWN BY	DATE	2:1	METRIC	COVER
▽=4	3 PLACES ± ---	± ---	CHECKED BY	DATE			
▽=0	2 PLACES ± 0.10	± ---	APPROVED BY	DATE	MOLEX INCORPORATED		
▽=0	1 PLACE ± 0.20	± ---	RBAUMAN	2011/04/18			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SEE TABLE		DOCUMENT NO.		SHEET NO.
			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SD-34843-400		1 OF 1