





Data sheet | Item number: 756-5311/030-050

Sensor/Actuator cable; M12A plug; straight; 3-pole; Length: 5 m

www.wago.com/756-5311/030-050



i Picture differs from the item.



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Data

Technical data

General

Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	2.5 kV
Contact resistance	10 mΩ
Conductor resistance	≤ 60 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Suitable for drag chains

Bending diameter (min.)	86
Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

Cable

Cable length	5 m
--------------	-----

Subject to changes. Please also observe the further product documentation!



Type code	LiF9YH-11YH or LiF9YC11YFHF
Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	4.1 ... 4.5 mm

Connector

Connection type	M12 plug - free end
Cable connection direction to mating direction	0°
Connector interface coding (cable/adaptor) 1 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	1 Nm

Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	HU
GTIN	4045454942069
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	8ea9dccc-d154-4b53-beb5-a124c113c453
SCIP notification number (Belgium)	cb7e1642-aa64-46da-82f3-7a777e380e2c
SCIP notification number (Bulgaria)	b482debe-4c8d-43da-9116-315bb4ed61d3
SCIP notification number (Czech Republic)	821baa26-44cd-4b82-a1bf-34261831c3be
SCIP notification number (Denmark)	a6ff9966-621c-4929-875e-0febe1d5cd15

Subject to changes. Please also observe the further product documentation!


WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.

SCIP notification number (Finland)	91fa3dba-9fcd-4e7e-983a-fa5f91bdd432
SCIP notification number (France)	3286f63e-5ef2-414f-800d-b76432abdf21
SCIP notification number (Germany)	9b050b19-b3dc-4b71-aebd-57b85d3302a4
SCIP notification number (Hungary)	cf3d3743e-013b-479e-a8a1-08bc4af88c4e
SCIP notification number (Italy)	29d2290e-9ae8-43fd-8236-e9031b6c2595
SCIP notification number (Netherlands)	ac6859ab-8cc2-46e2-a4b1-0741966d5afe
SCIP notification number (Poland)	95f9e867-dc3c-472f-8fae-1b0c2c72dfce
SCIP notification number (Romania)	402fc76d-feee-4877-9bbe-fdcc989204f7
SCIP notification number (Sweden)	754fd148-cd48-4841-ab6b-17b3b8a2923b

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Documentation

Bid Text

756-5311/030-050 X81 - Datei	2019 Feb 19	xml 3.3 kB	Download
756-5311/030-050 doc - Datei	2017 Sep 20	doc 26.1 kB	Download

System Description

IP67 Cables and Pluggable Connectors	pdf 161.6 kB	Download
--------------------------------------	-----------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 756-5311/030-050	URL	Download
---------------------------------	-----	----------

Subject to changes. Please also observe the further product documentation!



WSCAD Universe 756-5311/030-050

[URL](#)

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-5311/030-050

[URL](#)

[Download](#)

Sensor/Actuator cable; M12A plug; straight; 3-pole; Length: 5 m

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.