



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NUMBER	WEIGHT
NKA6PPG48Y	2.36 lb (1070.48 g)

- NOTES:
- SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AS WELL AS OPTIONAL ICONS.
 - MATERIAL:
 PANEL HOUSING: STEEL
 RJ45 MODULES: THERMOPLASTIC RESIN UL94V-0
 PUNCHDOWN BLOCKS: THERMOPLASTIC RESIN UL94V-0
 BEZEL ASSEMBLY: THERMOPLASTIC RESIN UL94H-B
 RETENTION CAP: THERMOPLASTIC RESIN UL94V-0
 - 48 PORT ANGLED PATCH PANEL 8 POSITION 8 WIRE.
 - THE PATCH PANEL IS DESIGNED FOR MOUNTING TO 19" UNIVERSAL RACKS.
 - FOUR (4) 12-24 X 1/2" ROUND HEAD SCREWS ARE PROVIDED FOR FASTENING TO RACKS.
 - DIMENSIONS IN BRACKETS ARE IN METRIC.
 - USE 110 STYLE TERMINATION TOOL FOR PUNCHDOWN.
 - RETENTION CAPS (ONE PER CONNECTOR) PROVIDED FOR SNAP-IN ON TERMINATED CONNECTORS.



PART NUMBER	SEE CHART	PRODUCT SPEC/PKG SPEC	N/A
I.I. NUMBER	N/A	WORK INSTRUCTION	N/A

TITLE
NETKEY CAT6 48 PORT ANGLED PATCH PANEL
 CUSTOMER DRAWING

ITEM REVISION NAME	M02088AN/01	PANDUIT
DATASET FILE NAME	M02088AN_DC44/01A	

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN (mm)		MATERIAL:
.x ± .1 [2.54]	.xxx ± .005 [0.127]	
.xx ± .01 [0.25]	ANGLES ± 5°	DRAWING NUMBER:
THIRD ANGLE PROJECTION		02088-44

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
2	10-1-18	BAME	KRKE	MMR	A. REMOVED M6 SCREWS	M09000HW
1	10-2-13	BJN	SCAL	JCK	ADDED NEW PANDUIT DRAWING FORMAT	02088-44
R	1-29-13	LZ	MBVE	JCK	RELEASED TO PRODUCTION	02088-44

DRAWN BY	DATE	CHK	SCALE	SHT 1 OF 1	SIZE
LZ	1-23-13	MBVE	.25:1		A

D10100DA/14