
THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



| ISSUE NUMBER | |
|--------------|--|
| ORIGINAL | |

(1)






NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, 30µ" GOLD PLATED

-55°C ~ 125°C 10A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



| | SW REFERENCE NO.: 629 C | OMBO ASSEMBLY | | |
|--------------------------------------|--|--------------------------|------------------|-------|
| COMBINATION D-SUB | | DRAWN: C.B | DATE: JAN. 01/20 | 19 |
| | | CHECKED: | DATE: | |
| EDAC INC | ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 |
| TORONTO, ONTARIO CANADA | | DRAWING NUMBER: 629-5W1- | ·640-1T4 | ISSUE |
| YOUR CONNECTION TO QUALITY & SERVICE | | PART NUMBER: 629-5W1- | 640-1T4 | 1 |



30.80 25.00

■16.90

°.©.°

ШЦ

 \bigcirc

۲

100



12.50 8.30

> THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



.X ±0.25 .XX ±0.13 .XXX ±0.05

OPERATING TEMPERATURE:

5000MΩ min.

1000V AC rms

