

## NOTES:

WITHSTANDING VOLTAGE:


MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING SIGNAL CONTACT RESISTANCE:	10A (CURRENT) 5: 5A PER CONTACT 10m0 MAX
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.

				SW REFERENCE NO.: 630 COMBO ASSEMBLY			
			DRAWN:	C.B	DATE: JAN. 01/20	19	
			CHECKED:		DATE:		
	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE:	(IN C.A.D. 1:1)	SHEET 1 OF	2	
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-3WK3640-1NE		ISSUE		
	YOUR CONNECTION TO QUALITY & SERVICE		PART NU	MBER: 630-3WK	3640-1NE	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY. 1000V AC rms

	9



.XX ±0.13

.XXX ±0.05

