۳ Q I	m		0	σ	>	
A Z						4
			LAYOUT SHOWN AS F	EXAMPLE		3
Kov	ng Shown as example					
CHARACTERISTICS						
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal					
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	ØS35.7 MaxZ31 MaxVV THREADM25x1-6g		SOURIAU shall not be liable for ar due to a use of the Products w he Specifications issued by either o (professional recommenda Count	hich does not comply with of the Parties or by a third p ition, technical notice.)	ontrol List	
 Contact Plating : Gold over copper Alloy 0.8µm minimum Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories 			PN: 8D517	1	ed	2
-Temperature Range : -65°C to +200°C		A 14-10-2016 Firs	t Release			
-Salt Spray : 48 hours						10
		ISS DATE Li Designed By:	atest modification - by Date:	CUSTON	MOD N	<u>'</u>
			Aluminium Plug 8D series			
→ BASIC SERIES: 8D 5 - 17 F 26 A → SHELL TYPE : Plug with RFI Shielding	D	SCALE	General linear Tolerances:		95 / PROJECT 859	1
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17	ORIENTATION : D CONTACT TYPE : PIN(500 Matings)	SOURIAU	WWW.SOURIAU.		document is the property of SOURIAU nust not be reproduced or	
		FORMAT			nunicated without permission SHEET	
PLATING : F = Nickel	CONTACT LAYOUT : 17-26	A3	SOURIAU		1/2	
			8D517F			
H G F	I E	D	C	B	Α	

