

IT-M7722L

Parameter	IT-M7722L	
AC Input		
Voltage	100 ~ 240Vac	
Phase	Single-phase	
Frequency	47 ~ 63Hz	
Max.current	8.5A	
Power factor	0.99 (Typical)	
AC Output		
Max. output power	600VA	
Max. output voltage	300Vac	
Output phase	Single-phase	
Current range(rms)	6A	
Current range(peak)	18A	
Output frequency range	45 ~ 100Hz	
Phase angle degree range	0 ~ 359.9°	
THD*1*3	≤0.3% at 45 ~ 100Hz	
Crest factor	3	
Line Regulation *3	≤0.06%	
Load Regulation *3	≤0.15%	
Output voltage (VAC)	Resolution	0.1V
	Accuracy	±(0.2%+0.2% F.S.)
Frequency	Resolution	0.1Hz
	Accuracy	±0.1%
Phase angle degree range	Resolution	0.1°
	Accuracy	0.5°
DC offset value	20mVdc	
Efficiency	80% (Typical)	
DC Output		
Max. output power	600W	
Max. output voltage	±400Vdc	
Maximum output current (rms)	±6A	

Parameter		IT-M7722L
DC voltage	Accuracy	±(0.2%+0.2% F.S.)
Dynamic response time (Full load of 10~90%)		≤0.5ms
Meter		
AC Voltage	Range	0 ~ 300V
	Resolution	0.1V
	Accuracy	±(0.25%+0.25% F.S.)
AC current (rms)	Range	0.1 ~ 6A
	Resolution	10mA
	Accuracy	±(0.25%+0.25% F.S.)
AC current (peak)	Range	0 ~ 8.5A
	Resolution	10mA
	Accuracy	±(0.4%+0.8% F.S.)
DC voltage	Accuracy	±(0.25%+0.25% F.S.)
DC current	Accuracy	±(0.25%+0.355% F.S.)
Frequency	Range	45 ~ 100Hz
	Resolution *4	0.1Hz
	Accuracy *2	±0.1%
Power (S)	Resolution	100mVA
	Accuracy	±(0.5%+0.5% F.S.)
Other		
Protection		OTP, OCP, OVP, OPP
Dimension (WxHxD)	Without foot post, protective cover	215 × 44.45 × 450 mm
	With foot post, protective cover	234 × 57.02 × 500 mm
Weight		5 KG

*1: Min voltage for THD test is 100Vac.

*2: Min voltage for frequency display accuracy is 100Vac.

*3: Tested with pure resistive load.

*4: The applicable range of frequency resolution is 45~99.9Hz.