# ATGBICS Juniper QFX-QSFP-DACBO-3M Compatible 40G QSFP+ to 4x10G SFP+ Direct Attach Copper Breakout Cable 3m Passive

**Brand :** ATGBICS

**Product code:** QFX-QSFP-DACBO-3M-C

**Product name :** Juniper QFX-QSFP-DACBO-3M Compatible 40G QSFP+ to 4x10G SFP+ Direct Attach Copper Breakout Cable 3m Passive

Juniper QFX-QSFP-DACBO-3M Compatible 40G QSFP+ to 4x10G SFP+ Direct Attach Copper Breakout Cable 3m Passive

ATGBICS Juniper QFX-QSFP-DACBO-3M Compatible 40G QSFP+ to 4x10G SFP+ Direct Attach Copper Breakout Cable 3m Passive:

ATGBICS QFX-QSFP-DACBO-3M compatible 40GBase QSFP+ to 4x10G SFP+ direct attach breakout cable operates over passive copper with a cable length of 3m. It is suitable for very short distances and provides a cost-efficient way to connect hardware within close proximity racks. This breakout cable connects to 1 x 40G QSFP+ port of a switch on one end and to 4 x 10G SFP+ ports of a switch on the other end. Our product is built to the exact specification of Juniper QFX-QSFP-DACBO-3M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 40G InfiniBand 8x DDR, 4x QDR, 10G/40Gigabit Ethernet, Fibre Channel. Connector A is QSFP+ MSA SFF-8436 Compliant and connector B is SFP+ MSA SFF-8431 Compliant.

| Features | |
|---|---|
| Product colour * | Black |
| Cable length * | 3 m |
| Connector 1 * | QSFP+ |
| Connector 2 * | 4x SFP+ |
| Connector 1 gender * | Male |
| Connector 2 gender * | Male |
| Jacket material | Polyvinyl chloride (PVC) |
| Conductor material | Copper |
| Ethernet interface type | 40 Gigabit Ethernet |
| Networking standards | IEEE 802.3ba |
| AWG wire size | 30 |
| Data transfer rate | 40000 Mbit/s |

| Features | |
|---|---|
| Plug and Play | ✓ |
| Certification | CE,FCC |
| **Operational conditions** | |
| Operating temperature (T-T) | 0 - 70 °C |
| Storage temperature (T-T) | -40 - 80 °C |
| Operating relative humidity (H-H) | 10 - 90% |
| Storage relative humidity (H-H) | 10 - 85% |
| **Packaging data** | |
| Quantity per pack | 1 pc(s) |
| **Technical details** | |
| Sustainability certificates | RoHS |

Publication date: 19-OCT-2021. Prints or copies of Information are only valid on the printed Publication date