## **HellermannTyton**

## **Specification Sheet**

Part Number: 156-03005

Clamp and mount combination means no extra hardware is needed, for time-saving, toolless, one-handed installation. Three size ranges handle diameters from 0.5" to 2", reducing part inventory.

Clamp saddle provides additional attachment option using a cable tie.

Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out.

serviced without removing it from the strut.

Quick2Clamp, 1.42" - 2.0" Bundle Dia, 1-5/8" Strut Attachment, PA66HIRHSUV, Black, 25/bag

Article Number156-03005TypeIRCDSTRUTColorBlack (BK)Quantity PerbagProduct DescriptionThe Quick2Clamp offers ultra-fast installation and versatility for<br/>managing conduit, tubing and cables. The built-in strut mount attaches<br/>with a simple twist. The one-piece design makes it simple to install. The<br/>robust, adjustable clamp closes by hand to the desired diameter. A<br/>release feature allows easy and nondestructive maintenance simply by<br/>using a flat-head screwdriver. In this way, the clamp can be reused or

Short Description	Quick2Clamp, 1.42" - 2.0" Bundle Dia, 1-5/8" Strut Attachment, PA66HIRHSUV, Black, 25/bag
Global Part Name	IRCDSTRUT-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	100.0
Length L (Imperial)	5.55
Length L (Metric)	140.9
Fixation Method	1-5/8 " Strut Attachment
Variant	Load Rating: 17 lbs, Safety Factor: 3 Pull Force Rating: 50 lbs
Width W (Imperial)	1.37
Width W (Metric)	34.81
Bundle Diameter Min (Imperial)	1.42
Bundle Diameter Min (Metric)	36.0
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	51.0
Height H (Imperial)	2.06
Height H (Metric)	52.4

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Certification/Specification	UL   UL2239 Conduit & Cable Hanger
UL Listed (US)	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.