## **HellermannTyton**

## **Specification Sheet**

Part Number: SNP1010M4



Snapper Hose Clamp, .57"-.65" Bundle Diameter, POM, White, 1000/pkg

Article Number	190-00046
Туре	SNP10
Color	White (WH)
Features & Benefits	• Installation and removal can be five times faster than conventional clamps . • Heat stabilized material is suitable for high temperature applications. • Completely reusable . • Will not rust or corrode . • Safety engineered. • No protruding band or cluster. • Can be installed with hose in place . • One-hand installation for tight places.
Quantity Per	bag

Pro	duct	Des	crip	tion
	auvi	-	91 . P	

Snapper Hose Clamps are lightweight and corrosion-resistant. Manufactured from high-performance thermoplastic materials selected to work well in a variety of diverse environments. A quick ratchet closure provides for reduced assembly line time and allows for application after connection of the hose. Release is achieved by initiating opposed lateral movement of the ratchet ends. Heat stabilized materials are available for high-temperature, motor, and under-hood applications. Snappers are also stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils, and greases. The Snapper is available in 32 standard sizes ranging from 1/4" to 4-1/2" ID. Snappers are manufactured in white polyacetal and black polyamide 6.6 glass filled impact modified heat stabilized material. Custom designed and different colored or shaped Snappers are available based upon applications and volume requirements.

Short Description	Snapper Hose Clamp, .57"–.65" Bundle Diameter, POM, White, 1000/pkg
Global Part Name	SNP10-POM-WH
Fixation Method	Plug-in mounting
Variant	Closed
Wall Thickness WT (Imperial)	.068
Wall Thickness WT (Metric)	1.7

Material	Polyacetal (POM)
Material Shortcut	POM
Flammability	UL 94 HB
UV Resistant (Yes/No)	No

Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $<sup>\</sup>hbox{@}$  2019 HellermannTyton. All Rights Reserved.