
# TRIPP-LITE

## Right Cover for DIN-Rail Mounting Enclosure Module, TAA

### MODEL NUMBER: N063-001-ENC-R









### Highlights

- Durable plastic construction recommended for industrial Ethernet network applications
- Right cover compatible with Tripp Lite N063-001-ENC-K1 enclosure module
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

#### **System Requirements**

N063-001-ENC-K1 DIN-Rail Mounting Enclosure Module

#### Package Includes

N063-001-ENC-R Right Cover for DIN-Rail Mounting Enclosure Module

Protects an industrial DIN-rail RJ45 Ethernet cable connection in harsh conditions.

module's snap-in keystone jack and cabling for protection in harsh conditions.

#### Features

**Gives Full Coverage to a DIN-Rail Network Cable Connection in Harsh Industrial Environments** The N063-001-ENC-R is a durable plastic right cover compatible with the Tripp Lite N063-001-ENC-K1 DIN-Rail Mounting Enclosure Module, which comes with a left cover. This cover allows full coverage of the

#### TAA-Compliant for GSA Schedule Purchases

The N063-001-ENC-R is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

## **Specifications**

OVERVIEW		
UPC Code	037332276926	
Technology	Cat5/5e; Cat6; Cat6a	
Firmware / Software Docs		
Offset Ports	No	
PHYSICAL		
Primary Form Factor	DIN-Rail	
Color	Gray	
Material of Construction	PC FR Plastic	
Total Number of Ports	1	

# TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

Shipping Dimensions (hwd / in.)	0.25 x 4.50 x 8.00	
Shipping Weight (Ibs.)	0.02	
Unit Dimensions (hwd / in.)	2.370 x 2.370 x 0.160	
ENVIRONMENTAL		
Operating Temperature Range	-13° to 122°F (-25° to 50°C)	
Storage Temperature Range	-40° to 158°F (-40° to 70°C)	
Operating Humidity Range	10% to 85% RH, Non-Condensing	
Storage Humidity Range	10% to 85% RH, (Non-Condensing)	
CONNECTIONS		
Number of Ports	1	
Side A - Connector 1	KEYSTONE JACK CUTOUT	
FEATURES & SPECIFICATIONS		
All-in-One Kit	No	
Antibacterial	No	
IP68 Rated	No	
IP20 Rated	No	
Numbered Ports	No	
Keystone Jacks	No	
Built-in Cables	No	
Color-Coded Connections	No	
EIA/TIA 2/32 Spacing	No	
Labeled Ports	No	
Down-Angled Ports	No	
Panel Applications	Ethernet	
STANDARDS & COMPLIANCE		
Product Compliance	CE (Europe); REACH; RoHS; UKCA; Trade Agreements Act (TAA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



1000 Eaton Boulevard Cleveland, OH 44122 United States



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.