



基板取付穴推奨寸法
 (基板厚: t=1~1.6mm)
 RECOMMENDED PC BOARD
 HOLE DIMENSION
 (THICKNESS: t=1~1.6mm)

注記
 NOTE

- △ 適合ターミナル: 50034 8*00
 APPLICABLE TERMINAL: 50034 8*00
- 2. 材料 ハウジング: ポリアミド, UL94V-0
 色: ナチュラル(白)
 MATERIAL HOUSING: POLYAMIDE, UL94V-0
 COLOR: NATURAL(WHITE)
- 3. ELV 及び RoHS 適合品
 ELV AND RoHS COMPLIANT.

18	20.4	51015 1000	10
16	18.4	0900	9
14	16.4	0800	8
12	14.4	0700	7
10	12.4	0600	6
8	10.4	0500	5
6	8.4	0400	4
4	6.4	0300	3
2	4.4	51015 0200	2
B	A	ORDER No.	極数 NO. OF CKT

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: OBSOLETE PART NUMBER AS PER PCN#509988	molex		
mm	8:1	EC NO: 704776 DRWN: SUGEEB CHK'D: GGA APPR: GGA			
GENERAL TOLERANCES (UNLESS SPECIFIED)			2.0 BOARD IN CONN HSG		
10 ^{UNDER}	±0.2	2022/04/08	PRODUCT CUSTOMER DRAWING		
10 ^{OVER} 30 ^{UNDER}	±0.25	2022/05/24	DOCUMENT NUMBER		
30 ^{OVER}	±0.3	2022/05/24	SD-51015-XX00		
ANGULAR ±3°		INITIAL REVISION:	DOC TYPE	DOC PART	REVISION
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DRWN: RFC_PLMIMP APPR: YOITO	PSD	020	D
		THIRD ANGLE PROJECTION	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
		DRAWING	SEE TABLE	GENERAL MARKET	1 OF 1
		SERIES	A3-SIZE		
		51015			