NEMA line Outlet 5-15R, Snap-in Mounting, Front Side, V-Slot Terminal





Description

- Panel mount :
- Snap-in , Front Side
- 1 Function :
- Line Outlet, Protection class I - V-Slot- Connector

See below: Approvals and Compliances

Characteristics

- Designed for standard applications

References Last order date: 15.12.2021

Weblinks

pdf data sheet, html datasheet, General Product Information, Approvals, Distributor-Stock-Check, Accessories, Detailed request for product

Technical Data

Ratings UL/CSA	15A / 125VAC; 60Hz
Allowable Operation Tempe-	-25 °C to +60 °C
rature	
IP-Protection	front side IP20 acc. to IEC 60529
Protection against electric	Suitable for appliances with protection
shock	class I acc. to IEC 61140
Terminal	V-Slot- Connector
Panel Thickness S	Snap-in 0.8mm to 1.6mm
Material: Housing	Thermoplastic, black

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 0709-1

Approval Logo	51	Certificates	Certification Body	Description
FL		UL Approvals	UL	UL File Number: E103791
SÞ		CSA Approvals	CSA	CSA Certification Record: 73165

0709-1

Product standards

Product standards that are referenced

FIOUUCI Stanuarus triat a			
Organization	Design	Standard	Description
IEC	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
IEC	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
(h)	Designed according to	UL 498	Standard for Attachment Plugs and Receptacles
CSA Group	Designed according to	CSA C22.2 no. 42	General Use Receptacles, Attachment Plugs, and Similar Wiring Devices

Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
IEC.	Designed for applications acc.	IEC/UL 62368-1	IEC 62368-1 includes the basic requirements for safety of audio, video, information technology and office equipment.


Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
50	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Dimensions [mm]





Panel thickness X 0.8 - 1.2 mm: 24.6 mm 1.3 - 1.6 mm: 24.8 mm

Assembly Instructions



Installation Diagram: V-slotted terminals for connecting multiple receptacles (only for solid bare wires from type 14 AWG)

All Variants

Туре	Protection Class	Panel mounting	Panel Thickness s [mm]	Terminal	Color	Order Number
0709-1	I	Snap-in	0.8 -1.6	V-Slot- Connector	black	4300.0702

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit	120 Pcs	
Mating Inlets/Plugs		

Category / Description

Power Supply Cord Overview complete



Cord Sets 16 A, Europlug, 2.5 m, Connector IEC C19, H05W-F3G1.5, black 6004.0395 Cord Sets 16 A, Interconnection, 1.0 m, Connector IEC C19, H05W-F3G1.5, black 6020.0392 Cord Sets 16 A, Interconnection, 2.0 m, Connector IEC C19, H05W-F3G1.5, black 6020.0394 Cord Sets 16 A, Interconnection, 2.0 m, Connector IEC C19, H05W-F3G1.5, black 6009.5195 Cord Sets 16 A, North America, 2.5 m, Connector IEC C19, SJT 3x18 AWG, black 6009.1315

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications. 29.03.2021