


THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	(1)







.X ±0.25 .XX ±0.13 .XXX ±0.05

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

(IF PRESENT)

STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED **OPERATING TEMPERATURE:**

-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

10A (CURRENT) POWER/CO-AX CONTACT RATING:

SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

5000MΩ min.

1000V AC rms



				SW REFERENCE NO.: 629 COMBO ASSEMBLY				
CC	COMBINATION D-SUB		DRAWN: C.B		DATE: JAN. 01/2019		19	
			CHECKED:		DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (I	IN C.A.D. 1:1)	SHEET 1	OF	2		
	TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS	DRAWING N	3250-1T4		ISSUE		
YOUR CONNECTION TO QUA	YOUR CONNECTION TO QUALITY & SERVICE		PART NUME	BER: 629-3WK	3250-1T4		1	



10.67

20033

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

