		т (П		0	₽	Þ]	
Image: standard is based on this 2899 series SUBRAU dual not be lable for any non-contromity or damage table for any non-contro	4						4	
CHARCTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material :: -Shell : Shell : -Shell : <td></td> <td></td> <td></td> <td>LAYOUT SHOWN AS EX</td> <td>XAMPLE</td> <td></td> <td>3</td>				LAYOUT SHOWN AS EX	XAMPLE		3	
CHARCTERISTICS -Standard : Based on MIL-DTL-38999 Series III -Shell Material :: -Shell : Shell : -Shell : <td></td> <td>Keving Shown as example</td> <td></td> <td></td> <td></td> <td></td> <td></td>		Keving Shown as example						
-Standard : Based on MIL-DTL-38999 Series III -Shell Material ::: Aluminium -Durability ::: :: Shell ::: Sh								
Shell Material :: Aluminium Shell Material :: Aluminium Shell Plating :: Kicklel								
Contact Plating :: Gold over copper Alloy 0.8µm minimum 2 -Durability :: 500 Mating cycles </td <td>-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy</td> <td>Z 31 Max</td> <td></td> <td>due to a use of the Products wh the Specifications issued by either of (professional recommendat</td> <td>ich does not comply with f the Parties or by a third party ion, technical notice.)</td> <td></td> <td></td>	-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy	Z 31 Max		due to a use of the Products wh the Specifications issued by either of (professional recommendat	ich does not comply with f the Parties or by a third party ion, technical notice.)			
Delivered with Souriau contacts and Accessories Temperature Range : -65°C to +200°C. Salt Spray : : 48 hours. Mass : : 29.9 g ± 10% Mass : : 29.9 g ± 10% BASIC SERIES: : : : : : : : : : : : : : : : : : :								
-Salt Spray : 48 hours -Mass : 29.9 g ± 10% BASIC SERIES: 8D 5 - 17 F 06 A C SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 PLATING : F = Nickel CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 17-06 CONTACT LAYOUT :								
-Salt Spray : 48 hours -Mass : 29.9 g ± 10% BASIC SERIES: 8D 5 - 17 F 06 A C SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 PLATING : F = Nickel CONTACT TYPE : PIN(500 Matings) CONTACT TYPE : PIN(500 Matings) C			A 14-10-2016	First Release				
BASIC SERIES: 8D 5 17 F 06 A C C Aluminium Plug 8D series Aluminium Plug 8D series 859 1 SHELL TYPE : Standard Crimp Contact ORIENTATION : C SOURIAU SOURIAU SOURIAU SOURIAU Sourcommunicated without permission 1 PLATING : F = Nickel CONTACT TYPE F = Nickel SOURIAU DRG N° SHEET SHEET SHEET SHEET SHEET SHEET SOURIAU SO							_	
BASIC SERIES: 8D 5 - 17 F 06 A C SCALe SCALe SCALe SCALe SCALe SSCALe SSCA					CUSTOMER DRAWI		†	
BASIC SERIES: BD 3 1			TITLE Aluminium Plug 8D series					
CONTACT TYPE : Standard Crimp Contact ORIENTATION : C SHELL SIZE : 17 CONTACT TYPE : PIN(500 Matings) PLATING : F = Nickel CONTACT LAYOUT : 17-06		A C		Tolerances:		Г	-	
PLATING : F = Nickel FORMAT SOURIAU DRG N° SHEET	CONTACT TYPE : Standard Crimp Contact		SUUKIAU	WWW.SOURIAU.C	SOURI/ it must not be re	AU produced or		
			·				-	
		CONTACT LATUUT . 17-00						
H G F E D C B A	Н	F F					7	

	т		G	н т	m	D		0	
		Contact	Layout						
4		•	+Y ⊕ ⊕ ^B } +X						
		Contact (Insert arrangen	-Y						
ယ	Shell Arrange size no. 17 -6	(mm) A +.121 (3.07 B +.241 (6.17 C +.000 (0.00 D241 (6.17 E121 (3.07 F +.000 (0.00 ment Number of Size contacts contact	(mm) (7) +.209 (5.31) (2) +.000 (0.00) (1) 241 (6.12) (2) +.000 (0.00) (7) +.209 (5.31) (1) +.000 (0.00) (2) +.000 (0.00) (3) +.000 (0.00) (4) Service (5) rating (5) Contact						
								SOURIAU shall not due to a use of the Specifications iss	the Products w sued by either c
N							[(professiona	al recommenda Count FR
						A IS Desi		6 First Release Latest modification - Date:	J: 8D517
									Alumir General linear Tolerances:
4								J WWW.S	± OURIAU.(
		1			 7				SOURIAU 8D517F
	Н		G	F	E	D		С	

