

UPS Input Cord Length (ft.)	3
UPS Input Cord Length (m)	0.9
BATTERY	
Expandable Runtime	Yes
DC System Voltage (VDC)	192
UPS Connection	Detachable cable with UPS specific DC connector (90 cm length)
Typical Battery Lifespan	4-6 years typical (North America)
PHYSICAL	
Material of Construction	Steel
Rack Height	2U
External Battery Pack Form Factor	Rack
Installation Form Factor Notes	Upright vertical tower configuration is not recommended for this model
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount
Installation Form Factors Supported with Optional Accessories	2 post rackmount (2 post rackmount 2POSTRMKITWM)
Minimum Required Rack Depth (cm)	58.42
Minimum Required Rack Depth (inches)	23
Shipping Dimensions (hwd / in.)	9.76 x 26.10 x 28.07
Shipping Dimensions (hwd / cm)	24.79 x 66.29 x 71.30
Shipping Weight (lbs.)	108.00
Shipping Weight (kg)	48.99
Unit Dimensions (hwd / in.)	3.430 x 17.320 x 19.830
Unit Dimensions (hwd / cm)	8,7 x 44 x 50,4
Unit Weight (lbs.)	75.20
Unit Weight (kg)	34.11
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe)
WARRANTY & SUPPORT	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty

Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available