


ERP610W152KYF0

Aliases (C834YF152K760X, ERP610VH4150KYF0)

Obsolete

ERP610 SFTY X1-760 Y1-500, Ceramic, 1500 pF, 10%, 760 VAC (X1), 500 VAC (Y1), Y5U, Lead Spacing = 10mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information	١			
Series	ERP610 SFTY X1-760 Y1-500			
Style	Radial Disc			
Description	Ceramic Single Layer Safety Disc Capacitors			
RoHS	Yes			
Termination	Tin			
Qualifications	UL, CSA, CAN, ENEC, VDE			
AEC-Q200	No			

,		
1500 pF		
10%		
760 VAC (X1), 500 VAC (Y1)		
-40/+125°C		
Y5U		
2.5%		
10 GOhms		
X1/Y1		

Click	here	for	the	3D	model.

Dimensions	
D	10mm MAX
т	5mm MAX
S	10mm NOM
LL	3mm +2mm
F	0.8mm +/-0.05mm
А	6mm MAX
V	2.1mm +/-0.5mm

Packaging Specifications

Packaging

Bulk, Bag

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.