



Note: '()' correspond to the letters used in the product bulletin

Click [here](#) for the 3D model.

### Dimensions

|           |                 |
|-----------|-----------------|
| Chip Size | 4036            |
| L         | 10.2mm +/-0.2mm |
| W         | 9.1mm +/-0.2mm  |
| T         | 5.5mm +/-0.2mm  |
| F         | 0.5mm NOM       |

### Packaging Specifications

|                    |     |
|--------------------|-----|
| Packaging          | T&R |
| Packaging Quantity | 800 |

### General Information

|                |                              |
|----------------|------------------------------|
| Series         | F161                         |
| Dielectric     | Metallized Polyester Stacked |
| Style          | SMD Chip                     |
| Features       | Automotive Grade             |
| RoHS           | Yes                          |
| Qualifications | AEC-Q200                     |
| AEC-Q200       | Yes                          |
| Shelf Life     | 104 Weeks                    |
| MSL            | 3                            |

### Specifications

|                       |                                    |
|-----------------------|------------------------------------|
| Capacitance           | 0.039 uF                           |
| Capacitance Tolerance | 10%                                |
| Voltage AC            | 200 VAC                            |
| Voltage DC            | 400 VDC                            |
| Temperature Range     | -55/+125°C                         |
| Rated Temperature     | 85°C                               |
| Dissipation Factor    | 0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz |
| Insulation Resistance | 1 GOhms                            |
| Max dV/dt             | 40 V/us                            |