

M4(300)-240X20M

Aliases (UFSM40030ET000)

KEMET, M4, Flex Suppressors, RFID

	T
	W
L	

Series M4

Style Sheet

Description Flex Suppressor Halogen Free Type

Features High Magnetic Permeability Type, Low Magnetic Loss Type

RoHS Yes

Qualifications UL94 HB, UL File No. E176124

Environment Halogen Free, PVC Free, Lead Free, Red Phosphorus Free

Specifications	
Temperature Range	-40/+105°C
Permeability	40 u At 13.56MHz
Effective Frequency	13.56 MHz and below
Specific Gravity	3.1TYP
Surface Resistivity	10 MOhm/sq. TYP

Click here for the 3D model.

Dimensions	
Sheet Size	240mmx20M
L	20000mm NOM
W	240mm NOM
Т	0.3mm NOM

Packaging Specifications	
Tape Description	No Adhesive Tape
Component Weight	4175.83 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.