

## Specification Sheet

Part Number: 156-01714



Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.

Clip is reusable, making relocation or adjustments simple.

All-in-one bundling and mounting solution reduces costs.

<b>Article Number</b>	156-01714
<b>Type</b>	T50SMVCLOC20-25
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	carton
<b>Product Description</b>	HellermannTyton's 1-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.
<b>Short Description</b>	LOC Locking Clamp, 20–25 mm, with T50SMVC Swivel Tie, PA66HIRHSUV, Black, 1000/ctn
<b>Global Part Name</b>	T50SMVCLOC20-25-PA66HIRHSUV-BK

<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	8.3
<b>Length L (Metric)</b>	210.0
<b>Fixation Method</b>	Omega Clips
<b>Identification Plate Position</b>	none
<b>Width W (Imperial)</b>	0.47
<b>Width W (Metric)</b>	12.0
<b>Bundle Diameter Min (Imperial)</b>	0.79
<b>Bundle Diameter Min (Metric)</b>	20.0
<b>Bundle Diameter Max (Imperial)</b>	0.98
<b>Bundle Diameter Max (Metric)</b>	25.0
<b>Height H (Imperial)</b>	1.53
<b>Height H (Metric)</b>	38.9
<b>Depth D (Imperial)</b>	0.47
<b>Depth D (Metric)</b>	12.0

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Material Cable Tie</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Flammability</b>	UL 94 HB
<b>Halogen Free</b>	Yes
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988