

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1718143006](#)
Status: **Active**
Overview: [KK Interconnect Solutions](#)
Description: KK 396 RPC Wire-to-Board Right-Angle Header with Friction Lock, 6 Circuits

Documents:

| | |
|--|--|
| 3D Model | Packaging Specification PK-171814-0001-001 (PDF) |
| Drawing (PDF) | Test Summary TS-171813-0001-001 (PDF) |
| 3D Model (PDF) | Test Summary TS-171814-0001-001 (PDF) |
| Product Specification PS-171813-0001-001 (PDF) | Symbol Footprint Data SYM-171814-0006-001 (PDF) |
| Product Specification PS-171813-0002-001 (PDF) | RoHS Certificate of Compliance (PDF) |



Agency Certification

| | |
|-----|---------|
| CSA | LR19980 |
| UL | E29179 |

General

| | |
|----------------|---|
| Product Family | PCB Headers |
| Series | 171814 |
| Application | Power, Signal, Wire-to-Board |
| Overview | KK Interconnect Solutions |
| Product Name | KK 396 |
| UPC | 887191718255 |

Physical

| | |
|--------------------------------|--------------------------------|
| Breakaway | No |
| Circuits (Loaded) | 6 |
| Circuits (maximum) | 6 |
| Color - Resin | Black |
| Durability (mating cycles max) | 25 |
| First Mate / Last Break | No |
| Flammability | 94V-1 |
| Glow-Wire Capable | No |
| Guide to Mating Part | No |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Nickel |
| Material - Resin | High Temperature Thermoplastic |
| Net Weight | 2.504/g |
| Number of Rows | 1 |
| Orientation | Right Angle |
| PCB Locator | No |
| PCB Retention | None |
| PCB Thickness - Recommended | 1.60mm |
| Packaging Type | Embossed Tape on Reel |
| Pitch - Mating Interface | 3.96mm |
| Plating min - Mating | 1.524µm |
| Polarized to Mating Part | Yes |
| Shrouded | Partial |
| Stackable | No |
| Surface Mount Compatible (SMC) | Yes |
| Temperature Range - Operating | -40° to +105°C |
| Termination Interface: Style | Through Hole |

Electrical

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2021)4569-DC (8
July 2021)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[171814 Series](#)

Mates With

[2145](#) , [41815](#) , [6442](#) , [2139](#) , [41695](#) , [3069](#)

| | |
|-------------------------------|-------|
| Current - Maximum per Contact | 13.0A |
| Voltage - Maximum | 600V |

Solder Process Data

| | |
|--|----------|
| Duration at Max. Process Temperature (seconds) | 030 |
| Lead-free Process Capability | SMC&WAVE |
| Max. Cycles at Max. Process Temperature | 003 |
| Process Temperature max. C | 260 |

Material Info**Reference - Drawing Numbers**

| | |
|-------------------------|--|
| Packaging Specification | PK-171814-0001-001 |
| Product Specification | PS-171813-0001-001, PS-171813-0002-001 |
| Sales Drawing | SD-171814-0001-000, SD-171814-0001-002 |
| Symbol/Footprint Data | SYM-171814-0006-001 |
| Test Summary | TS-171813-0001-001, TS-171814-0001-001 |

This document was generated on 10/05/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION