

BUSHING

2X SCREW AND LOCK WASHER

2X LATCH SEGMENT 2X RECOMMENDED TORQUE: 1.5-2.0 NM-

BACKSHELL

NOTES: UNLESS OTHERWISE SPECIFIED


1. RECEPTACLE MATERIAL: SHELL: ZINC ALLOY, NICKEL PLATED INSERT AND RETAINING RING: THERMOPLASTIC SEAL: SILICONE RUBBER


2. BACKSHELL MATERIAL: SHELL: ALUMINIUM ALLOY, NICKEL PLATED: LATCH SEGMENT: ALUMINIUM ALLOY, NICKEL PLATED; SCREW AND LOCK WASHER: STAINLESS STEEL;

BUSHING: EPDM.

3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE: IP67 & IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. APPLY TO CABLE OD SIZE: Ø11.20-Ø24.08 . CAN BE USED:
 - 4.1. WITH LARGE AND SMALL BUSHINGS IN PLACE.
 - 4.2. WITH ONLY LARGE BUSHING IN PLACE.
- 4.3. WITH BOTH BUSHINGS REMOVED.
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6. SEE SPECIFIC RECEPTACLE DRAWING FOR:
 - 6.1 CONTACT SIZE AND WIRE RANGE.
 - 6.2 RETAINING RING COLOR.
- 6.3 MATING PART(S).
- 6.4 CONTACT LAYOUT AND ALL OTHER SPECIFICATIONS.





AHDM04-24-16SR-059 HD34-24-16SR-059 PART NUMBER DESCRIPTION ITEM QUANTITY MATERIALS LIST UNLESS OTHERWISE SPECIFIED SIGNATURES DATE Amphenol J. HEAD 10NOV2020 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036 MATERIAL SPECIFICATIONS CUSTOMER DURAMATE AHDM RECEPT, SIZE 24, WD THD, KIT W/ CABLE CLAMP BACKSHELL THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DA'S HOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION NO RIGHOR FRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS. B C-AHDM04-24-16SR-059 NEXT ASS'Y CALE: NONE SHEET 1 OF 1

KIT, RECPT AND BACKSHELL, SZ 24 DWG NO: AHDM04-24-16SR-059

REV: A1

SH: