

PRIMARY: 1004221319

Use capacitance gauge and run FFT:

1. SRL: VoP : 70%; Core Dia.: 0.0126; Outer Dia.: 0.0354"
2. Display SRL: X-Axis: 0-25 GHz; Y-Axis: -50 to 0 dB
3. Display Spectrograph: Y-Axis (SRL Freq. Range): 1-25 GHz; Value Range (Color Spectrum): -35 to -20
4. Flag if Spectrograph is showing solid color <-32 dB

LONGITUDINAL FOIL SHIELD: 1000680085

HELICAL FOIL

LAY LENGTH (LH) / ANGLE / OVERLAP	0.100" / 62 degrees / 43%
-----------------------------------	---------------------------

HEAT SEALED JACKET TDR & VNA CHECK

Print Legend (Drain Wire Side): MOLEX TEMP-FLEX(R) <LOCATION CODE: US OR PHL OR GDL>
 TWINMAX(TM) 28 AWG 1000680085 --- E61522 <UL CODE: -MPI for PHL, <blank> for US, -MDM for GDL>
 STYLE 22058 cRUus AWM I A/B 105C 30V FT1 VW-1 --- <TRACEABILITY>

<TRACEABILITY> = LOT/Batch#, Mfg. Date (format: YYYYMMDD) Sequential Footage Marking.

LAY LENGTH (RH) / ANGLE / OVERLAP	0.100" / 62 degrees / 43%
-----------------------------------	---------------------------

ELECTRICAL

TDR & VNA CHECK

1 start sample per spool. Length = 13ft 1.5 in. (4m)

LENGTHS REQUIRED	LENGTHS PER SPOOL	MIN. LENGTH	SPLICE CODE	SPOOL SIZE
Any	1	1000'	N/A	12X7X5