

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Right-Angle Cat6 Gigabit Snagless Molded Slim UTP Ethernet Cable (RJ45 M/M), Blue, 2 ft. (0.61 m)

MODEL NUMBER: N201-SR2-BL



Connects network components like printers, computers, copiers, routers, servers, modems and switches. Ideal for high-density data centers. Slim design increases airflow in tight spaces.

Description

The N201-SR2-BL Cat6 Gigabit Molded Slim UTP Patch Cable is perfect for connecting network components like printers, computers, copiers, routers, servers, modems and switches in high-density data centers. Designed for fast transmission and excellent signal quality, this 2-ft. (0.61 m) blue cable ensures peak performance throughout your local area network (LAN).

Manufactured from 28 AWG copper wire, the four-pair stranded UTP N201-SR2-BL delivers speeds up to Cat6 Gigabit/1 Gbps. Protected by a PVC jacket, this cable is more than 35% smaller in diameter than standard Cat6 cable, which increases airflow in tight spaces and makes it easier to install around corners and through cable management panels.

Space-saving right-angle RJ45 male connectors are easy to plug into patch panels and switches located in adjoining spaces inside a rack. Integral strain relief ensures the cable and connectors last a long time.

Features

Perfect Solution for Your Networking NeedsIdeal for connecting components like printers, computers, copiers, routers, servers, modems and switches in high-density data centersDesigned for fast transmission and excellent signal qualityEnsures peak performance throughout your LANDelivers speeds up to Cat6 Gigabit/1 Gbps

No-Snag Right-Angle RJ45 ConnectorsMale connectors plug easily into patch panels and switches in adjoining rack spacesMolded boots protect locking tabs from damage during installation

Special Slim DesignMore than 35% smaller in diameter than standard Cat6 cableIncreases airflow in tight spacesIncreased flexibility for installing around corners and through cable management panels

Premium Construction for Superior PerformanceMade from 28 AWG copper wirePVC 4-pair stranded UTPIntegral strain relief for long life

Specifications

Highlights

- Over 35% slimmer than standard Cat6 cables
- Rated for Cat6 Gigabit/1 Gbps communications
- Right-angle RJ45 male connectors
- Easy to route through cable management panels
- High-quality 28 AWG stranded copper wire

Package Includes

 N201-SR2-BL Cat6 Gigabit Molded Slim UTP Patch Cable (M/M), 2-ft. (0.61 m)



UPC Code 03732139674 Technology Caf6 PHYSICAL Edual Color Blue Cable Jacket Material PVC Cable Jacket Material PVC Cable Jacket Rating CM Cable Shelding UTP Cable Outer Diameter (OD) 4.0mm Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 28 AWG Cable Length (ft.) 2 Cable Length (ft.) 2 Cable Length (ft.) 2 Cable Length (ft.) 24 Shipping Dimensions (ftwd / rm.) 7.00 x 9.00 x 0.50 Shipping Weight (fdg) 0.03 Shipping Weight (fdg) 0.03 Shipping Weight (fdg) 0.07 EnvironNEMENTAL 14 to 140 F (-10 to 60 C) Carlarge Temperature Range 14 to 18 F (-20 to 70 C)		
Technology Cal6 PHYSICAL Color Blue Cable Jacket Material PVC Cable Scheiding Cable Jacket Material PVC Cable Scheiding Cable Scheiding UTP Cable Outer Diameter (OD) Admin Amm Cable Outer Diameter (OD) Number of Conductors 4 Pair Cable Outer Diameter (OD) Conductor Range 28 AWG Cable Conductor Gauge Cable Length (t) 2 Cable Length (t) Cable Length (th) 24 Cable Length (th) Cable Length (th) 24 Cable Length (th) Shipping Dimensions (twd / n) 17.78 x 22.86 x 1.27 Shipping Dimensions (twd / n) 7.00 x 9.00 x 0.50 Shipping Weight (tbs.) 0.07 EnviroNMENTAL Operating Temperature Range VerkTownerTal 14 to 140 F (-10 to 60 C) Storage Temperature Range 14 to 158 F (-20 to 70 C) Relative Humidity Range 10% TO 90% RH. Non-Condesing Storage Temperature Range 10% TO 90% RH. Non-Condesing Storage Temperature Range 10% TO 90% RH. Non	OVERVIEW	
PHYSICAL Color Blue Color Blue Cable Jacket Material PVC Cable Jacket Rating CM Cable Shelding UTP Cable Duter Diameter (OD) 4.0mm Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 28 AWG Cable Length (IL) 2 Cable Length (IL) 17.78 x 22.86 x 1.27 Shipping Dimensions (INV of (IN) 7.00 x 9.00 x 0.50 Shipping Veight (Ites) 0.03 Shipping Weight (Ites) 0.07 Environmental Environmental Coparing Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperatu	UPC Code	037332193674
Color Blue Cable Jacket Material PVC Cable Jacket Raing CM Cable Shielding UTP Cable Shielding UTP Cable Outer Diameter (OD) 4.0mm Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Material Stranded Copper Conductor Material Stranded Copper Cable Length (ft.) 2 Cable Length (fn.) 24 Cable Length (m) 0.61 Cable Length (m) 61 Shipping Dimensions (mvd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (mvd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.07 Environmentatu 0.07 Environmentatu 14 to 140 F (-10 to 60 C) Storage Temperature Range 14 to 140 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Communicatrions 250 MHz <tr< td=""><td>Technology</td><td>Cat6</td></tr<>	Technology	Cat6
Cable Jacket Material PVC Cable Jacket Rating CM Cable Shielding UTP Cable Cuter Diameter (OD) 4.0mm Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 28 AWG Cable Longth (ft.) 2 Cable Longth (ft.) 2 Cable Longth (ft.) 24 Cable Length (cm) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Weight (bs.) 0.07 ENVERNMENTAL 0.03 Shipping Weight (bs.) 0.07 ENVERNMENTAL 0.07 Storage Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range 14 to 158 F (-20 to 70 C) Relative Humidity 10% - 09% RH, Non-Condesing Conductor Compatibility Range 10% TO 90% RH, Non-Condesing CommUNICATIONS 250 MHz<	PHYSICAL	
Cable Jacket Rating CM Cable Shielding UTP Cable Outer Diameter (OD) 4.0mm Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 28 AWG Cable Longth (ft.) 2 Cable Longth (ft.) 2 Cable Longth (ft.) 61 Cable Longth (m.) 64 Cable Longth (m.) 61 Cable Longth (m.) 7.00 x 8.00 x 6.50 Shipping Dimensions (hwd / om) 17.78 x 22.86 x 1.27 Shipping Unimensions (hwd / om) 7.00 x 8.00 x 6.50 Shipping Veight (kg.) 0.07 Environmentatur 0.07 Environmentatur 0.07 Operating Temperature Range 14 to 140 F (-10 to 66 C) Storage Temperature Range 14 to 138 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Storage Kumidity Ran	Color	Blue
Cable Shielding UTP Cable Outer Diameter (OD) 4.0mm Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 28 AWG Cable Length (ft.) 2 Cable Length (m) 0.61 Cable Length (m) 24 Cable Length (m) 24 Cable Length (m) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Veight (kg) 0.03 Shipping Veight (kg) 0.03 Shipping Veight (kg.) 0.07 Enviroommetrature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range 14 to 158 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Length the rTIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Cable Jacket Material	PVC
Cable Outer Diameter (OD) 4.0mm Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 28 AWG Cable Length (ft.) 2 Cable Length (m) 0.81 Cable Length (m) 0.81 Cable Length (m) 0.81 Cable Length (m) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / cm) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.03 Shipping Weight (kg) 0.07 ENVIRONMENTAL Dora Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range 4 to 158 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Communications 250 MHz Network Compatibility 1 Gbpa (Gigabit) IEEE Standards Supported 802.3an	Cable Jacket Rating	CM
Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 28 AWG Cable Length (ft.) 2 Cable Length (m) 0.61 Cable Length (m) 24 Cable Length (m) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / cm) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.03 Shipping Weight (kg) 0.03 Shipping Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range 14 to 158 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Communications 250 MHz Relative Humiditit per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 302.3an	Cable Shielding	UTP
Conductor Material Stranded Copper Conductor Gauge 28 AWG Cable Length (ft.) 2 Cable Length (m) 0.61 Cable Length (m) 24 Cable Length (m) 61 Cable Length (m) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / cm) 7.00 x 9.00 x 0.50 Shipping Dimensions (hwd / lm.) 7.00 x 9.00 x 0.50 Shipping Weight (bs.) 0.07 EnvironMentAL Veronomous (block of colds) Shipping Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range 14 to 158 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Communications 250 MHz Relative Humidity Range 260 MHz Network Compatibility 1 Sps (Gigabil) IEEE Standards Supported 802.3an	Cable Outer Diameter (OD)	4.0mm
Conductor Gauge 28 AWG Cable Length (t.) 2 Cable Length (m) 0.61 Cable Length (m) 61 Cable Length (cm) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (bs.) 0.07 ENVIRONMENTAL 0.07 Porating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Temperature Range 10% TO 90% RH, Non-Condesing COMUNICATIONS 250 MHz Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Number of Conductors	4 Pair
Cable Length (ft.) 2 Cable Length (m) 0.61 Cable Length (m) 24 Cable Length (cm) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.03 Shipping Weight (kg.) 0.07 ENVIRONMENTAL 0.07 Environmentation of the total of the to	Conductor Material	Stranded Copper
Cable Length (m) 0.61 Cable Length (m.) 24 Cable Length (cm) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / n.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.03 Shipping Weight (ks.) 0.07 ENVIRONMENTAL 0.07 Coperating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range 4 to 158 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Temperature Range 10% TO 90% RH, Non-Condesing Communications 250 MHz Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Conductor Gauge	28 AWG
Cable Length (in.) 24 Cable Length (cm) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.03 Shipping Weight (kg) 0.07 ENVIRONMENTAL 0.07 Storage Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% - 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Temperatures 10% TO 90% RH, Non-Condesing Storage Time Ti A Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Cable Length (ft.)	2
Cable Length (cm) 61 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.03 Shipping Weight (kg) 0.07 ENVIRONMENTAL 0.07 Environmental 14 to 140 F (-10 to 60 C) Storage Temperature Range 14 to 140 F (-10 to 60 C) Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Temperature Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Storage Temperature Storage 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Cable Length (m)	0.61
Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / cm) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.03 Shipping Weight (bs.) 0.07 ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing COMMUNICATIONS Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Cable Length (in.)	24
Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.03 Shipping Weight (bb.) 0.07 ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing ENVIRONCATIONS 250 MHz Retwork Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Cable Length (cm)	61
Shipping Weight (kg) 0.03 Shipping Weight (bs.) 0.07 ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Etel Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Shipping Dimensions (hwd / cm)	17.78 x 22.86 x 1.27
Shipping Weight (lbs.) 0.07 ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing COMMUNICATIONS Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Shipping Dimensions (hwd / in.)	7.00 x 9.00 x 0.50
ENVIRONMENTAL Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing COMMUNICATIONS 250 MHz Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Shipping Weight (kg)	0.03
Operating Temperature Range 14 to 140 F (-10 to 60 C) Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing COMMUNICATIONS 10% TO 90% RH, Non-Condesing Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Shipping Weight (lbs.)	0.07
Storage Temperature Range -4 to 158 F (-20 to 70 C) Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing COMMUNICATIONS 10% TO 90% RH, Non-Condesing Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	ENVIRONMENTAL	
Relative Humidity 10% ~ 90%, NON-CONDENSING Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing COMMUNICATIONS 10% TO 90% RH, Non-Condesing Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Operating Temperature Range	14 to 140 F (-10 to 60 C)
Operating Humidity Range 10% TO 90% RH, Non-Condesing Storage Humidity Range 10% TO 90% RH, Non-Condesing COMMUNICATIONS COMMUNICATIONS Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Storage Temperature Range	-4 to 158 F (-20 to 70 C)
Storage Humidity Range 10% TO 90% RH, Non-Condesing communications	Relative Humidity	10% ~ 90%, NON-CONDENSING
COMMUNICATIONS Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Operating Humidity Range	10% TO 90% RH, Non-Condesing
Bandwidth per TIA Standard 250 MHz Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	Storage Humidity Range	10% TO 90% RH, Non-Condesing
Network Compatibility 1 Gbps (Gigabit) IEEE Standards Supported 802.3an	COMMUNICATIONS	
IEEE Standards Supported 802.3an	Bandwidth per TIA Standard	250 MHz
CONNECTIONS	Network Compatibility	1 Gbps (Gigabit)
	IEEE Standards Supported	802.3an
Side A - Connector 1 P 145 (MALE)	CONNECTIONS	
	Side A - Connector 1	RJ45 (MALE)



Side B - Connector 1	RJ45 (MALE)	
Crossover Wiring	No	
Contact Plating	Gold	
Connector Type	Snagless	
Wiring Configuration	EIA/TIA 568B	
FEATURES & SPECIFICATIONS		
IP68 Rated	No	
Snagless Connector	Yes	
Antibacterial	No	
STANDARDS & COMPLIANCE		
Certifications	RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies