|   |  | 10                              | 9  | 8  | 7   |          | 6                      |                                   | 5                                       | 4   | 3  |
|---|--|---------------------------------|--|--|---|----------|------------------------|-----------------------------------|---|---|--|
|   | MATERIA<br>1300611   |                                 | NEERING NUMBER FINISHED LENGTH<br>3007K13M100 10.0 METER   |  |   |          |                        |                                   |   |   |  |
| F |  |                                 |  |  | 1.78 REF-   |          | 25                     | SHED LEN<br>±.125<br>RAP<br>BEL   | GTH                                     |   |  |
| E |  |                                 |  | 1.70 REF   |   |          | PER STD-314            | 6                                 |   |   |  |
| D |  |                                 |  | 5-WHITE  |   |          | }                      | $\overline{\boldsymbol{\lambda}}$ |   |   |  |
| С | NDTES:<br>1. MATERIAL: SEE TABLE<br>2. FINISHES: SEE TABLE |                                 |  |  |   |          |                        |                                   |   |   |  |
| В | 6  | 4.                              | ELECTRICAL SPECIFICA<br>ASSEMBLY IS RDHS CON<br>ASSEMBLY IS UL RECOO   | 1PLIANT  |   | IMENT C2 | 2/16/09<br><br>3/02/17 | QUALITY                           |   | L TOLERANCES<br>S SPECIFIED)<br>mm INCH P   | DIMENSION STYLE<br><br>RAWN BY DATE  |
| A | 5<br>4<br>3<br>2<br>1<br>ITEM                              | A/R<br>1<br>3<br>1<br>SEE TABLE | PVC MOLDING COMPOUND<br>MALE COUPLING NUT<br>MALE PIN CONTACT<br>3P MALE INSERT<br>#16/3 FLEX CABLE<br>DESCRIPTION | PVC<br>ZINC ALLOY<br>COPPER<br>POLYURETHANE<br>TPE COMPOUND JACKET<br>MATERIAL | YELLOW<br>BLACK E-COAT<br>GOLD PLATE<br>BLACK<br>YELLOW<br>FINISH | B        | <br>2009-01<br>RELL    |                                   | 3 PLACES<br>2 PLACES<br>1 PLACE<br>ANGU | ±     ±     M       ±     ±     CF       ±     ±     R       ±     ±     AF       JLAR ±°     R       ERE APPLICABLE     M/ | ODELL 2008/10   IECKED BY DATE   DEROSS 2008/10   PROVED BY DATE   DEROSS 2008/10   VERIAL NO. SEE TABLE   IZE THIS DRAWING   INCORPORATED |
|   |  | 10                              | 9  | 8  | 7   |          | 6                      |                                   | 5                                       | 4   | 3  |

| 3                                   |  |         | 2         |            |         | 1     |                   |   |
|-------------------------------------|--|---------|-----------|------------|---------|-------|-------------------|---|
|                                     |  |         |           |            |         |       |                   | F |
|                                     |  |         |           |            |         |       |                   | E |
|                                     |  |         |           |            |         |       |                   | D |
|                                     |  |         |           |            |         |       |                   | с |
| YLE                                 |  | SCALE   | DESIGN    | UNITS<br>- | 0       | THIRE | ) ANGLE<br>ECTION | В |
| 008/10/27<br>008/10/27<br>008/10/27 | 16/3 TPE CABLE<br><br>molex MOLEX INCORPORATED<br>DOCUMENT NO. SHEET NO. |         |           |            |         |       |                   |   |
| BLE<br>WING CON<br>ATED AND         |  | IS INFO | RMATION . | THAT IS F  | ROPRIET |       |                   |   |