











2.54

.XX ±0.13

.XXX ±0.05

## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYES STEEL, TIN PLATED COPPER ALLOY, GOLD FL	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)	
SIGNAL CONTACT CURRENT RATING SIGNAL CONTACT RESISTANCE:		
INSULATOR RESISTANCE:	5000MΩ min.	
DIELECTRIC		
WITHSTANDING VOLTAGE:	1000V AC rms	

		SW REFERENCE NO.: 630 COMBO ASSEMBLY		
COMBINATION D-SUB	DRAWN: C.B	DATE: JAN. 01/201	9	
	CHECKED:	DATE:		
EDAC INC TORONTO, ONTARIO CONTARIO	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
	DRAWING NUMBER: 630-5W1	-240-3T4	ISSUE	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



EDAC INC CANADA

OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: C.B DATE: JAN. 01/2019   CHECKED: DATE:   SCALE: (IN C.A.D. 1:1) SHEET 1 OF 2   DRAWING NUMBER: 630-5W1-240-3T4 ISSUE   PART NUMBER: 630-5W1-240-3T4 1	SW REFERENCE NO.: 630 COMBO ASSEMBLY		
SCALE: (IN C.A.D. 1:1) SHEET 1 OF 2 DRAWING NUMBER: 630-5W1-240-3T4 ISSUE	DRAWN: C.B	DATE: JAN. 01/2019	
DRAWING NUMBER: 630-5W1-240-3T4 ISSUE	CHECKED:	DATE:	
1	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2	
PART NUMBER: 630-5W1-240-3T4 1	DRAWING NUMBER: 630-5W1-240-3T4 ISSUE		

## ISSUE NUMBER

