

R533I310050P0K

Aliases (5331310050P0K)

R53 X2 310 VAC, Film, Metallized Polypropylene, Automotive Safety, 0.1 uF, 10%, 310 VAC (X2), 630 VDC, 110°C, Lead Spacing = 15mm



Click here for the 3D model.

Dimensions	
L	18mm +/-0.5mm
Н	11mm +0.3/-0.5mm
т	5mm +0.3/-0.5mm
S	15mm +/-0.4mm
LL	25mm +2/-1mm
F	0.8mm +/-0.05mm

Packaging Specifications		
Packaging	Bulk, Bag	
Packaging Quantity	1000	

General Information	
Series	R53 X2 310 VAC
Dielectric	Metallized Polypropylene
Style	Radial
Features	Automotive Grade, EMI Safety
RoHS	Yes
Lead	Wire Leads
Safety Class	X2
Qualifications	ENEC, UL, cUL, CQC, AEC-Q200
AEC-Q200	Yes
THB Performance	Yes
Component Weight	1.2 g

Specifications		
Capacitance	0.1 uF	
Capacitance Tolerance	10%	
Voltage AC	310 VAC (X2)	
Voltage DC	630 VDC	
Temperature Range	-40/+110°C	
Rated Temperature	110°C	
Dissipation Factor	0.3% 1KHz	
Insulation Resistance	100 GOhms	
Max dV/dt	400 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.