REV	CHANGE	DATE	DRN	СНК
	Drawn	02/23/17	SJ	Т

	TOLERANCE DETAILS			
1	Α	+ 0.020 [+ 0.50] -0.000 [-0.00]		
2	В	±0.015 [±0.40]		
3	С	$\pm 0.015 [\pm 0.40]$		
4	D	+0.010 [+0.30]		



			TM	
Ø 3/16 — [4.76] (A)	DIAMOND - KNURL	3/8 [9.53] (B)	3/4 ————————————————————————————————————	#6-32 THREAD.
rial · Stainless Steel	1/32 X 45° CHAMFER		1-1/8 [28.58] (C)	

NOTES:

1. Material : Stainless Steel

2. Finish:

3. ASME Y14.5M - 2009

All Drawing Dimensions are in Inches [mm]
 Unless otherwise specified; Edge Breaks, Radii or Countersinks 0.005-0.015



95 Silvermine Rd.,Seymour CT 06483 Tel: 203-888-2133,Fax: 203-888-9860

This Drawing is the Property of RAF. It contains confidential, proprietary information that is RAF property. Do not disclose to or duplicate for others except as authorized by RAF.

	TOLERANCES
	ALL DIMENSIONS ARE INCHES
(l	UNLESS OTHERWISE SPECIFIED)
	METALLIC
L	ENGTHS =: 6 INCHES ± 0.005</th
	LENGTH >: 6 INCHES ± 0.010

LENGTH >: 6 INCHES ±0.010
DIAMETERS: ±0.005
NON-METALLIC
LENGTH: ±0.010 DIAMETERS: ± 0.010 INTERNAL THREADS:
MINIMUM THREAD DEPTH

7454 00	SCALE
7151-SS	3.73
PUSH TYPE THUMB SCREWS	SHEET
	1 of 1

THUMB SCREWS

COMPONENT