



General Information		
Series	GR900 SMD Space	
Style	SMD Chip	
RoHS	No	
Prop 65	WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	01642942-375f-41b6-87dc-aef6906a9224	
Termination	Lead (SnPb)	
Failure Rate	N/A	
Testing and Reliability	GR900 CSAM A	
AEC-Q200	No	
Shelf Life	78 Weeks	
MSL	1	

Click here for the 3D model.

Dimensions	
Chip Size	2225
L	5.59mm +/-0.38mm (0.22 in +/-0.015 in)
W	6.35mm +/-0.38mm (0.25 in +/-0.015 in)
т	2.03mm MAX (0.08 in MAX)
В	0.51mm +/-0.25mm (0.02 in +/-0.01 in)

Specifications			
Capacitance	0.22 uF		
Capacitance Tolerance	10%		
Voltage DC	50 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	BX		

Packaging Specifications

Packaging

T&R, Plastic Tape

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.