

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
B		ECR-15-014706	10OCT2015	DL	CW
BI		ECR-15-016505	11NOV2015	DL	CW
C		ECR-17-007409	25MAY2017	DL	CW
D		ECR-21-117384	12NOV2021	WQR	CW

M3 SCREW, RECOMMENDED
TIGHTENING TORQUE 0.5Nm
M3螺丝, 推荐扭力矩为0.5Nm

M3 SCREW, RECOMMENDED
TIGHTENING TORQUE 0.5Nm
M3螺丝, 推荐扭力矩为0.5Nm

NOTES:

1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 400 V
RATED CURRENT: 10 A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 6 KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.14-2.5 mm² (26-14 AWG)
CONTACT TYPE: CRIMP CONTACT

2. CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20200X10XX00)

注释:

1. 技术参数:
绝缘材料: PC
额定电压: 400V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 6KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: 0.14-2.5 mm² (26-14 AWG)
接线类型: 冷压接

2. 端子需要单独订购.
(订货号参考图面: T20200X10XX00)

GROUNDING CONTACT TYPE: SCREW CONTACT
GROUNDING CONTACT FINISH: SILVER PLATED
WIRE RANGE: 2.5mm² (AWG14)
接地针类型: 螺丝压接
接地针表面处理: 镀银
接线范围: 2.5mm² (AWG14)

T2080122101-000	HQ-012-M	HQ-012 MALE INSERT HQ-012 公插
PART NUMBER 料号	PART DESCRIPTION 描述	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 31MAR2015 DAVID LI	TE Connectivity	
		CHK 31MAR2015 CHRIS WANG		
		APVD 31MAR2015 XU XIANG	NAME HQ-012-M	
DIMENSIONS: mm		PRODUCT SPEC 108-137114	RESTRICTED TO	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC 108-137114	SIZE A3	CAGE CODE -
MATERIAL		WEIGHT -	DRAWING NO T2080122101000	
FINISH		SCALE 2:1		SHEET 1 OF 1
-		CUSTOMER DRAWING		REV D

1470-19 (3/13)