				0	Ψ		
Contact Fully SUBJUCT SHOWN AS EXAMPLE Contact of dimension Standard: lased on Multiparts Dim Nonline Shell Plating: Black Zrin Nickel Dim Nonline Shell Plating: Black Zrin Nickel Dim Nonline Shell Plating: Sold Nick 100-188909 Series III Dim Nonline Shell Plating: Sold Rick 200 Kills Sold Nick 200 Series Dim Dim Sold Science Nonline Nonline Dim Nonline Dim Dim Sold Science Sold Nick 200 Series Dim Dim Dim Dim Dim Sold Science Sold Over cooper Alloy 0.8µm minimum Dim Dim Dim Dim Dim Dim Optication Science Sold Over cooper Alloy 0.8µm minimum Dim Dim Dim Dim Dim Dim Dim Optication Science Sold Over cooper Alloy 0.8µm minimum Dim							4
CHARACTERSTICS Standard: Based on MIL-DTL 38999 Series III. Shell Material i: duminium Heil Plaiting :: Black Zinc Nickel Heil Plaiting :: Customer Heil Plaiting :: Cus	ω			LAYOUT SHOWN A	S EXAMPLE		3
Standard : Based on MIL-DTL-38999 Series III Sine Material Sine Materia	CHARACTERISTICS						
No -Contact Plating :: Gold over copper Alloy 0.8µm minimum 2 -Durability :: 500 Mating cycles Not Listed 2 -Delivered without Souriau contacts -Delivered without Souriau contacts Not Listed 2 -Temperature Range :: 657 C to ±175 °C -Salt Spray :: 500 hours - <t< th=""><th>-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic</th><th>DimNominalØS25 MaxZ31 Max</th><th></th><th colspan="3">due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party</th><th></th></t<>	-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic	DimNominalØS25 MaxZ31 Max		due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party			
-Temperature Range :: -65°C to +175°C -Salt Spray :: 500 hours -Mass :: 15.06 g ± 10% BASIC SERIES: 80 5 - 11 Z 98 S C L SHELL TYPE :: Plug with RFI Shielding CONTACT TYPE :: Standard Crimp Contact SHELL SIZE :: 11 PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLATING :: Z = Black Zinc Nickel CONTACT TYPE :: SOCKET(500 Matings) PLAT	 -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles 			F	FR Not L		2
BASIC SERIES: 8D 5 11 Z 98 S C L BASIC SERIES: 8D 5 11 Z 98 S C L SHELL TYPE : Plug with RFI Shielding 0	-Salt Spray : 500 hours		ISS DATE	Latest modification - by	CUST		 N°
Addit Services: abb 3							
SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) SOURIAU it must not be reproduced or communicated without permission PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-98 FORMAT SOURIAU DRG N° SHEET	SHELL TYPE : Plug with RFI Shielding	Delivered W/O	Contacts NA	-[(859 This document is the property of	1
	SHELL SIZE : 11	CONTACT TYPE : SOCKET(500 I	Matings)		cc	it must not be reproduced or ommunicated without permission	
H G F E D C B A			A3	8D511	Z98SCL-C	1/2	

	Ŧ	പ	п –	m	D	<u>о</u>
4	-x	Contact Layout $A \oplus B \oplus $				
	Cont posit II A B C C D E F Shell Arrangement Numb size no. conta	A +.000 (0.00) +.130 (3.30) i +.130 (3.30) +.000 (0.00) i +.130 (3.30) +.000 (0.00) i +.065 (1.65) 113 (2.87) i 130 (3.30) +.000 (0.00) i 000 (0.00) +.000 (0.00)	1			
ယ	size no. conta 11 -98 6					
	 -					SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either
2						(professional recommend Cour Ff PN: 8D511
					A 18-10-20 ISS DATE Designed By:	16 First Release
<u> </u>					SCALE NA	Alum General linear Tolerances: ±
			_		FORMAT A3	SOURIA 8D5112
	Н	G	l F	I E	D	C

σ		A				
				4		
				3		
any non-conformit which does not co r of the Parties or b dation, technical no ntry Jurisd R 1298SCL	mply with by a third part			2		
	CUSTOME	R DRAWING	MOD N°			
iinium Plug 8D series						
r	NPRDS / PROJECT 859					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
U DRG N° Z98SCL-C			SHEET 2/2			
B		A	-			