



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-----------------|
| L | 13mm -0.5mm |
| H | 9mm -0.5mm |
| T | 4mm -0.5mm |
| S | 10mm +/-0.4mm |
| LL | 17mm +0/-1mm |
| F | 0.6mm +/-0.05mm |
| G | 0.5mm NOM |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 2200 |

General Information

| | |
|------------------|---|
| Series | F463 |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | MKP, Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Component Weight | 0.812 g |
| Miscellaneous | The Rated Voltage Decreases 2%/C Between +85C And +105C (1.25%/C For AC). ClimCat: 55/105/56. |
| Notes | Series Replaced by R75. |

Specifications

| | |
|-----------------------|---------------------------------------|
| Capacitance | 1200 pF |
| Capacitance Tolerance | 10% |
| Voltage AC | 700 VAC |
| Voltage DC | 2000 VDC, 1200 VDC (105C) |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.04% 1kHz, 0.06% 10kHz, 0.25% 100kHz |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 10000 V/us |
| Inductance | 6 nH |