
## **BGA Heat Sink - High Performance Straight Fin w/Thermal Tape**





ATS Part#: ATS-54330K-C1-R0

Description: 33.00 x 33.00 x 14.50 mm BGA Heat Sink - High Performance Straight Fin

w/Thermal Tape

Heat Sink Type: Straight Fin
Heat Sink Attachment: Thermal Tape

Equivalent Part Number: ATS-54330K-C2-R0

\*Image above is for illustration purpose only.

## **Features & Benefits**

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Designed specifically for BGAs and other surface mount packages
- · Comes preassembled with high performance thermal interface material

## **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 5.8 °C/W            | 4.4 °C/W            | 3.7 °C/W            | 3.3 °C/W            | 3 °C/W              | 2.8 °C/W            | 2.6 °C/W            |
|                    | Ducted Flow   | 3.2                 | N/A                 | N/A                 | N/A                 | N/A                 | N/A                 | N/A                 |

## **Product Detail**

| Schematic Image                                | Dimension A   | Dimension B   | Dimension C  | Dimension D   | TIM                                       | Finish                              |
|--|---|---|--|---|---|-------------------------------------|
|  | 33.00 mm  | 33.00 mm  | 14.50 mm   | N/A mm  | T412                                      | BLACK-ANODIZED                      |
| *Image above is for illustration purpose only. | <ul> <li>Dimension</li> <li>ATS-5433 (Saint-Go</li> <li>Thermal papplicatio</li> <li>ATS reserver</li> <li>ATS certification</li> </ul> | bain C675).<br>performance data ar<br>n.<br>rves the right to upd | height from the botto<br>act heat sink assem<br>e provided for refere<br>ate or change its pro | nbly with an equivalence only. Actual peroducts without notices -6 and REACH cores. | ent thermander<br>rformander<br>e to impr | al interface material e may vary by |



