

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

12-Outlet Power Strip with Surge Protection, 15-ft. Cord, 1050 Joules, 36 in. length

MODEL NUMBER: \$\$3612











Highlights

- 12 outlets
- 15-ft. cord
- 36-in. length
- 1050-joule rating

Package Includes

- SS3612 Power Strip/Surge Suppressor
- Set of adjustable mounting clips
- · Warranty information
- Instruction manual

Description

The SS3612 power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 12 NEMA 5-15R outlets with 2.48-in. center-to-center spacing, 15-ft. AC line cord and adjustable mounting clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 1050 joules. This corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket.

Features rugged all-metal housing, lighted power switch with transparent quard to prevent accidental

Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray housing with black output receptacles.

PLUG/OUTLETS: Input: NEMA 5-15P Output: 12 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: 3-ft. corded vertical/raceway power distribution strip

SURGE SUPPRESSION: 1050 joules

Features

- 3-ft. power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more
- Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 1050 joules
- 12 NEMA 5-15R outlets with 2.48-in. center-to-center spacing
- 15-ft. AC line cord
- Adjustable mounting clips for installation in a wide variety of applications
- Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket
- · Rugged all-metal housing



- Lighted power switch with transparent guard to prevent accidental shutoff
- 15A resettable circuit breaker
- Attractive gray housing with black output receptacles

Specifications

OVERVIEW		
UPC Code	037332186409	
ОИТРИТ		
Frequency Compatibility	60 Hz	
Output (Watts)	1800	
Output Receptacles	(12) 5-15R	
Circuit Breaker (amps)	15	
Outlet Spacing	2.48-in. center-to-center spacing	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	22000	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	15	
Right-Angle Plug	No	
Input Cord Length (m)	4.57	
Integrated Cord Clip	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	No	
Switches	Combination AC circuit breaker and lighted 2-position power switch controls power to all outlets	
Locking Switch Cover	Transparent locking switch cover	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1050	
UL1449 Let Through Rating	500V UL verified	
Auto Shut-Off	No	



DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping Dimensions (hwd / in.)	2.50 x 4.60 x 39.80	
Shipping Dimensions (hwd / cm)	6.35 x 11.68 x 101.09	
Shipping Weight (lbs.)	3.90	
Shipping Weight (kg)	1.77	
Unit Dimensions (hwd / in.)	1.25 x 1.62 x 36	
Unit Dimensions (hwd / cm)	3.18 x 4.11 x 91.44	
Included Mounting Accessories	Set of adjustable mounting clamps	
Integrated Keyhole Mounting Slots	No	
Receptacle Color	Black	
Color (AC Line Cord)	Black	
Color	Silver	
Outlets Measurement (Center to Center)	2.48	
Anti-Microbial Protected	No	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd EDITION	
UL1363 (Power Tap)	UL1363	
Canada	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies