

.XX ±0.13


.XXX ±0.05


10.70

5.80










NOTES:

| MATERIAL: HOUSING: SHELL: CONTACT: | THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED | |
|--|---|--|
| OPERATING TEMPERATURE: | -55°C ~ 125°C | |
| POWER/CO-AX CONTACT RATING: (IF PRESENT) | 20A (CURRENT) | |
| SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE: | | |
| INSULATOR RESISTANCE: | 5000MΩ min. | |
| DIELECTRIC WITHSTANDING VOLTAGE: | 1000V AC rms | |

| COMBINATION D-SUB | | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | |
|--|--|--------------------------------------|------------------|-------|
| | | DRAWN: C.B | DATE: JAN. 01/20 | 19 |
| | | CHECKED: | DATE: | |
| EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 |
| | | DRAWING NUMBER: 630-2W2- | -650-2N6 | ISSUE |
| | | PART NUMBER: 630-2W2- | -650-2N6 | 1 |



THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

J

COMPLIANT

