



RECOMMENDED MOUNTING HOLE PATTERN FOR 1.57 THICK P.C. BOARD

- PINS TO COMPLY WITH AMP SOLDERABILITY SPEC 109-11-3.
- MATES WITH PLUG P/N 770587-1.
- COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- RECOMMENDED FOR EDGE MOUNTING.
- 0.00381 MIN MATTE TIN LEAD OVER 0.00127 MIN NICKEL.
- 0.00076 MIN GOLD PLATE IN THE LOCALIZED GOLD PLATE AREA, 0.00381 MATTE TIN LEAD IN THE LOCALIZED PLATE AREA, BOTH OVER 0.00127 MIN NICKEL.
- 0.00381 MIN MATTE TIN OVER 0.00127 MIN NICKEL.
- 0.00076 MIN GOLD PLATE IN THE LOCALIZED GOLD PLATE AREA, 0.00381 MIN MATTE TIN IN THE LOCALIZED TIN PLATE AREA, BOTH OVER 0.00127 MIN NICKEL.
- SUPERSEDED BY 1-794108-1

1.00	.039	6.10	.240	51.26	2.018
0.76	.030	5.99	.236	22.771	.8965
0.25	.010	5.33	.210	18.631	.7335
0.13	.005	5.08	.200	14.491	.5705
0.08	.003	4.14	.163	12.70	.500
0.064	.0025	3.86	.152	10.351	.4075
0.05	.002	3.68	.145	9.80	.386
0.00381	0.000150	2.070	.0815	7.34	.289
0.00127	0.000050	1.57	.062	6.86	.270
0.00076	0.000030	1.40	.055	6.210	.2445
MM	IN	MM	IN	MM	IN

CONVERSION TABLE

BRASS	GOLD	8	NYLON, UL94V-0	WHITE	1-794108-1	
BRASS	TIN	7	NYLON, UL94V-0	WHITE	1-794108-0	
BRASS	GOLD	6	NYLON, UL94V-0	WHITE	-794108-2-	
OBSOLETE	BRASS	TIN-LEAD	5	NYLON, UL94V-0	WHITE	-794108-1-
MATERIAL	FINISH		MATERIAL	COLOR	PART NO.	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD	DATE
0 PLC ± -	1 PLC ± -	C. JONES	24JUL03
2 PLC ± 0.13	3 PLC ± -	C. JONES	24JUL03
4 PLC ± -	ANGLES ± -		

STE TE Connectivity

NAME: HEADER ASSEMBLY, RIGHT ANGLE, W/SHORT PEG, 24 CIRCUIT, MINI UNIVERSAL MATE-N-LOK(TM)

SIZE: A1 | CASE CODE: 00779 | DRAWING NO: 794108 | RESTRICTED TO: -

CUSTOMER DRAWING | SCALE: 5:1 | SHEET: 1 OF 1 | REV: D2