ATGBICS AFCT-5765ATLZ Avago Broadcom Compatible Transceiver SFP, 100Base-FX (1310nm, SMF, 15km, DOM, Ind Temp)

Brand: ATGBICS Product code: AFCT-5765ATLZ-C

Product name: AFCT-5765ATLZ Avago Broadcom Compatible Transceiver SFP, 100Base-FX (1310nm, SMF, 15km, DOM, Ind Temp) ATGBICS ATP01-31SL10DI
1315cm SMF 10m DOMLC
PC CE MMS ATT0234032421

AFCT-5765ATLZ Avago Broadcom Compatible Transceiver SFP, 100Base-FX (1310nm, SMF, 15km, DOM, Ind Temp)

ATGBICS AFCT-5765ATLZ Avago Broadcom Compatible Transceiver SFP, 100Base-FX (1310nm, SMF, 15km, DOM, Ind Temp):

ATGBICS AFCT-5765ATLZ 100Base-LX supports a distance of up to 15km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC connector. This product is suitable for rugged environments and can operate at temperatures between -10C to +85C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Avago Broadcom AFCT-5765ATLZ= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Douformanco		Dower	
Performance SFP transceiver type * Maximum data transfer rate * Interface type * Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM)	Fiber optic 100 Mbit/s SFP	Input voltage Maximum voltage Power consumption (typical) Operational conditions Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions	3.3 V 3.5 V 1.3 W -10 °C 85 °C -10 - 85 °C -40 - 85 °C 5 - 85% 5 - 85%
Wavelength-division multiplexing (WDM)	×	Width Depth Height	13.4 mm 56.5 mm 8.5 mm
Features		Weight	25 g
Product colour Housing material Plug and Play Hot-Plug support Hot-swap Easy to install Country of origin Brand compatibility Silver Metal		Packaging data Number of products included Package type	1 pc(s) Box
	Technical details Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead	
Certification	CE, FCC, RoHS	DOCSII (COIICAIII	Leau



5056468768506

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.