

Note: This datasheet may be out of date. Please download the latest datasheet of GJM0225C1C5R5BB01# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

http://www.murata.com/en-us/products/productdetail?partno=GJM0225C1C5R5BB01%23

GJM0225C1C5R5BB01L



< List of part numbers with package codes > GJM0225C1C5R5BB01L

Applications

Unsuitable Please be sure to read and comply with Applications these "Precautions for use." Consumer equipment.Industrial	
· · · · · · · · · · · · · · · · · · ·	
Consumer equipment Industrial	
Concentration of a principal and the	
Equipment,Mobile Electronics,Medical	
equipment [GHTF A/B/C] except for	
implant equipment,Automotive	
infotainment/comfort equipment	
Specific Please refer to Our Website and	
Applications specifications, etc. for information about	
the performance, functions, quality,	
management, and safety required for	
the above applications, and use	
Products after confirming the	
performance and reliability of the actual	
Product.	



Packaging	Specifications	Standard Packing Quantity
L	180Embossed Tape	40000

Aass (typ.)		
1 piece	0.09mg	

Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GJM0225C1C5R5BB01L

Note: This datasheet may be out of date. Please download the latest datasheet of GJM0225C1C5R5BB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GJM0225C1C5R5BB01%23

"#" indicates a package specification code.



Specifications

Length	0.4±0.02mm
Width	0.2±0.02mm
Thickness	0.2±0.02mm
Capacitance	5.5pF ±0.1pF
Distance between external terminals g	0.13mm min.
External terminal size e	0.07 to 0.14mm
Operating Temperature Range	-55℃ to 125℃
Rated Voltage	16Vdc
Size code in inch(mm)	01005 (0402M)
TC	0±30ppm/°C
Temperature characteristics (complied standard)	C0G(EIA)
Temperature range of temperature characteristics	25℃ to 125℃

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

